

2005

5.0 Watt - 28 Volts, Class C
Microwave 2000 MHz


GENERAL DESCRIPTION

The 2005 is a COMMON BASE transistor capable of providing 5 Watts Class C, RF output power at 2000 MHz. Gold metalization and diffused ballasting are used to provide high reliability and supreme ruggedness. The transistor uses a fully hermetic High Temperature Solder Sealed package.

ABSOLUTE MAXIMUM RATINGS

Maximum Power Dissipation @ 25°C	20 Watts
Maximum Voltage and Current	
BVces Collector to Emitter Voltage	50 Volts
BVebo Emitter to Base Voltage	3.5 Volts
Ic Collector Current	1.0 A
Maximum Temperatures	
Storage Temperature	- 65 to + 200°C
Operating Junction Temperature	+ 200°C

CASE OUTLINE 55BT-1, Style 1



ELECTRICAL CHARACTERISTICS @ 25 °C

SYMBOL	CHARACTERISTICS	TEST CONDITIONS	MIN	TYP	MAX	UNITS
P _{out}	Power Out	F = 2 GHz	5.0			Watt
P _{in}	Power Input	V _{cb} = 28 Volts			0.8	Watt
P _g	Power Gain	P _o = 5.0 Watts	8.0	8.5		dB
η _c	Collector Efficiency	As Above		40		%
VSWR ₁	Load Mismatch Tolerance	F = 2 GHz, P _o = 5 W			30:1	

BVces	Collector to Emitter Breakdown	I _c = 20 mA	50			Volts
BVcbo	Collector to Base Breakdown	I _c = 2 mA	45			Volts
BVebo	Emitter to Base Breakdown	I _e = 2.0 mA	3.5			Volts
Icbo	Collector to Base Current	V _{cb} = 28 Volts			1.0	mA
h _{FE}	Current Gain	V _{ce} = 5 V, I _c = 200 mA	20			
Cob	Output Capacitance	F = 1 MHz, V _{cb} = 28 V		7.5		pF
θ _{jc}	Thermal Resistance				8.5	°C/W


Issue August 1996

GHz TECHNOLOGY INC. RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE. GHz RECOMMENDS THAT BEFORE THE PRODUCT(S) DESCRIBED HEREIN ARE WRITTEN INTO SPECIFICATIONS, OR USED IN CRITICAL APPLICATIONS, THAT THE PERFORMANCE CHARACTERISTICS BE VERIFIED BY CONTACTING THE FACTORY.


GHz Technology Inc. 3000 Oakmead Village Drive, Santa Clara, CA 95051-0808 Tel. 408 / 986-8031 Fax 408 / 986-8120

POWER OUTPUT VS FREQUENCY

V_{cc}=28V, Pin = 0.8 Watts




EFFICIENCY VS FREQUENCY



POWER OUTPUT VS POWER INPUT


V_{cc}=28V



SMITH CHART

2005

NORMALIZED IMPEDANCE AND ADMITTANCE COORDINATES



NORMALIZED TO A 50 OHM SYSTEM.