


### Description

#### BNC 50 Ohm Cable Plug - Short Crimp Straight



### Ordering Data


#### BNC 50 Ohm Cable Plug - Short Crimp Straight

Part Number	Cable RG-/U	Crimp Tool Hex		Dimension A		Finish	Assembly Instructions	Note
		mm	in.	mm	in.			
28P107-1	58, 141	5.41	0.213	29.77	1.172	Silver	AI-26	
28P107-2	59, 62, 140	6.48	0.255	29.77	1.172	Silver	AI-26	
28P107-3	55, 142, 223	5.41	0.213	29.77	1.172	Silver	AI-26	
28P107-5	122, 180, 195	4.52	0.178	29.77	1.172	Silver	AI-26	
28P184-1	174, 179, 316	4.52	0.178	29.77	1.172	Nickel	AI-125	
28P270-6	58, 303	5.41	0.213	28.58	1.125	Silver	AI-334	1
28P270-8	59	6.48	0.255	28.58	1.125	Silver	AI-334	1
28P270-10	55, 142, 223, 400	5.41	0.213	28.58	1.125	Silver	AI-110	1

Note 1 - Captive Contact

### Description

#### BNC 50 Ohm Cable Plug - Short Crimp Right-Angle



### Ordering Data

#### BNC 50 Ohm Cable Plug - Short Crimp Right-Angle

Part Number	Cable RG-/U	Crimp Tool Hex		Dimension				Finish	Assembly Instructions	Note
		mm	in.	A		B				
				mm	in.	mm	in.			
28P150-1	58, 141	5.41	0.213	38.89	1.531	26.19	1.031	Silver	AI-26	
28P150-2	59, 62, 140	6.48	0.255	38.89	1.531	26.19	1.031	Silver	AI-26	
28P150-3	55, 142, 223	5.41	0.213	38.89	1.531	26.19	1.031	Silver	AI-26	
28P150-5	122, 180, 195	4.52	0.178	38.89	1.531	26.19	1.031	Silver	AI-26	
28P271-5	59, 62, 210	6.48	0.255	42.07	1.656	26.19	1.031	Silver	AI-26	1
28P271-6	58, 303	5.41	0.213	42.06	1.656	26.19	1.031	Silver	AI-26	1
28P271-7	142, 223, 400	5.41	0.213	42.06	1.656	26.19	1.031	Silver	AI-26	1

Note 1 - Captive Contact