

European "Pro Electron" Registered Types

**CNY30, CNY34
Optoisolator**

T-41-87


**GaAs Infrared Emitting Diode and
Light Activated SCR**

The CNY30 and CNY34 consist of a gallium arsenide, infrared emitting diode coupled with a light activated silicon controlled rectifier in a dual-in-line package. These devices are also available in surface-mount packaging.

absolute maximum ratings: (25°C)

INFRARED EMITTING DIODE			
Power Dissipation (-55°C to 50°C)	*100	milliwatts	
Forward Current (Continuous) (-55°C to 50°C)	60	milliamps	
Forward Current (Peak) (-55°C to 50°C) (100 μs 1% duty cycle)	1	ampere	
Reverse Voltage (-55°C to 50°C)	6	volts	
*Derate 2.0mW/°C above 50°C.			

PHOTO-SCR			
Off-State and Reverse Voltage (-55°C to 100°C)	CNY30 200 CNY34 400	volts	
Peak Reverse Gate Voltage (-55°C to 50°C)	6	volts	
Direct On-State Current (-55°C to 50°C)	300	milliamps	
Surge (non-rep) On-State Current (-55°C to 50°C)	10	amps	
Peak Gate Current (-55°C to 50°C)	10	milliamps	
Output Power Dissipation (-55°C to 50°C)**	400	milliwatts	
**Derate 8mW/°C above 50°C.			



TOTAL DEVICE	
Storage Temperature Range	-55°C to 150°C
Operating Temperature Range	-55°C to 100°C
Normal Temperature Range (No Derating)	-55°C to 80°C
Soldering Temperature (10 seconds)	260°C
Total Device Dissipation (-55°C to 50°C)	450 milliwatts
Linear Derating Factor (above 50°C)	9.0mW/°C
Surge Isolation Voltage (Input to Output)	3535V(peak) 2500V(RMS)
Steady-State Isolation Voltage (Input to Output)	3180V(peak) 2250(RMS)

individual electrical characteristics (25°C) (unless otherwise specified)

INFRAREMITSINGDIODE	TYP.	MAX.	UNITS
Forward Voltage V_F ($I_F = 10mA$)	1.1	1.5	volts
Reverse Current I_R ($V_R = 3V$)	-	10	microamps
Capacitance C_j ($V = 0, f = 1 MHz$)	50	-	picofarads

PHOTO-SCR	MIN.	MAX.	UNITS
Peak Off-State Voltage - V_{DM} ($R_{GK} = 10K\Omega, T_A = 100^\circ C$)	CNY30 200 CNY34 400	-	volts
Peak Reverse Voltage - V_{RM} ($T_A = 100^\circ C$)	CNY30 200 CNY34 400	-	volts
On-State Voltage - V_T ($I_T = 300mA$)		1.3	volts
Off-State Current - I_D ($V_D = 200V, T_A = 100^\circ C, I_F = 0, R_{GK} = 10K$)	CNY30	50	microamps
Off-State Current - I_D ($V_D = 400V, T_A = 100^\circ C, I_F = 0, R_{GK} = 10K$)	CNY34	150	microamps
Reverse Current - I_R ($V_R = 200V, T_A = 100^\circ C, I_F = 0$)	CNY30	50	microamps
Reverse Current - I_R ($V_R = 400V, T_A = 100^\circ C, I_F = 0$)	CNY34	150	microamps

coupled electrical characteristics (25°C)

	MIN.	MAX.	UNITS
Input Current to Trigger $V_{AK} = 50V, R_{GK} = 10K\Omega$	-	20	milliamps
Isolation Resistance $V_{AK} = 100V, R_{GK} = 27K\Omega$	100	11	milliamps
Turn-On Time - $V_{AK} = 50V, I_F = 30mA, R_{GK} = 10K\Omega, R_L = 200\Omega$	-	-	gigaohms
Coupled dv/dt, Input to Output (See Figure 13)	500	50	microseconds
Input to Output Capacitance ($V_{IO} = 0, f = 1 MHz$)	-	2	volts microsec. picofarads

VDE Approved to 0883/6.80 0110b Certificate # 35025

CNY30, CNY34

TYPICAL CHARACTERISTICS




FIGURE 1. INPUT CURRENT TO TRIGGER VS. ANODE-CATHODE VOLTAGE




FIGURE 2. INPUT CURRENT TO TRIGGER VS. TEMPERATURE




FIGURE 3. INPUT CURRENT TO TRIGGER DISTRIBUTION VS. TEMPERATURE




FIGURE 4. INPUT CURRENT TO TRIGGER VS. PULSE WIDTH




FIGURE 5. TURN-ON TIME VS. INPUT CURRENT




FIGURE 6. INPUT CHARACTERISTICS I_F VS. V_F

European "Pro Electron" Registered Types

CNY30, CNY34

TYPICAL CHARACTERISTICS OF OUTPUT (SCR)




FIGURE 7. HOLDING CURRENT VS. TEMPERATURE




FIGURE 9. OFF-STATE FORWARD CURRENT VS. TEMPERATURE




FIGURE 11. dv/dt VS. TEMPERATURE




FIGURE 8. MAXIMUM TRANSIENT THERMAL IMPEDANCE




FIGURE 10. ON-STATE CURRENT VS. MAXIMUM ALLOWABLE TEMPERATURE




FIGURE 12. ON-STATE CHARACTERISTICS


European "Pro Electron" Registered Types

CNY30, CNY34

TYPICAL APPLICATIONS


10A, T²L COMPATIBLE, SOLID STATE RELAY

Use of the CNY34 for high sensitivity, 2500V isolation capability, provides this highly reliable solid state relay design. This design is compatible with 74, 74S and 74H series T²L logic systems inputs and 220V AC loads up to 10A.



25W LOGIC INDICATOR LAMP DRIVER

The high surge capability and non-reactive input characteristics of the device allow it to directly couple, without buffers, T²L and DTL logic to indicator and alarm devices, without danger of introducing noise and logic glitches.



400V SYMMETRICAL TRANSISTOR COUPLER

Use of the high voltage PNP portion of the CNY34 provides a 400V transistor capable of conducting positive and negative signals with current transfer ratios of over 1%. This function is useful in remote instrumentation, high voltage power supplies and test equipment. Care should be taken not to exceed the CNY34 400 mW power dissipation rating when used at high voltages.




FIGURE 13
COUPLED dv/dt - TEST CIRCUIT

$V_p = 800$ Volts
 $t_p = .010$ Seconds
 $f = 25$ Hertz
 $T_A = 25^\circ$ C

