



Material:

- \* Insulation: High Temperature plastic UL 94V-0
- \* Contact: Brass
- \* Shell: Brass
- \* Shell Plating: Nickel over all plating

Ordering Code:

CU05 S C H 1 F 0A  
 ① ② ③ ④ ⑤ ⑥ ⑦

- ① Series No.
- ② S= Socket
- ③ Plating option:  
C= Selective 0.76μm(30μ") Gold plated over 1.27μm(50μ") Nickel
- ④ Tail Style: H= Right angle
- ⑤ Insulator color: 1= Black
- ⑥ Type: F= Flat type
- ⑦ Option: 0A= Standard

Recommended P.C. Board Layout

Lead Free Process  
 RoHS Compliant

④					DATE	UNIT: mm / inch	TITLE: IEEE 1394 FLAT R/A DIP RECEPTACLE CONNECTOR	瀚荃股份有限公司 CviLux Corporation
③					DRAWN BY: Karen 7/30-14'	TOLERANCE UNLESS OTHERWISE SPECIFIED	MATERIAL:	
②					ENGINEER: Sun 7/31-14'	.X ±0.38/.015 X' ± 1'	FINISH:	DRAWING NO. CU0512SB PART NO. CU05SCH1FOA
①	Karen	7/29-14'	ECNT114156/ECRT114063	CHECKED BY: Eisley 8/04-14'	APPROVED BY: David 8/04-14'	.XX ±0.25/.010 X' ±		SCALE 3 / 1
SYM	NAME	DATE	REVISIONS			.XXX ±0.13/.005 XX' ±		SHEET 1 OF 1