


MICRO ELECTRONICS

MI32T
INFRARED
EMITTING
DIODE

DESCRIPTION

MI32T is GaAlAs infrared emitting diode molded in 3mm diameter clear transparent lens.



- All dimension in mm(inch)
- No Scale
- Tol. : +/-0.3mm

ABSOLUTE MAXIMUM RATINGS

Forward Current (Continuous)
 Pulse Forward Current
 Reverse Voltage (Continuous)
 Power Dissipation
 Operating Temperature Range
 Lead Soldering Temperature (1/16" from body)

100mA
 1A*
 6V
 160mW
 -25 to +85°C
 260°C for 5 sec.

* Pulse Width = 10μs, Duty Ratio = 0.01.

ELECTRO-OPTICAL CHARACTERISTICS (Ta=25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	CONDITIONS
Radiant Power Output	Po		0.5		mW	IF=20mA
Forward Voltage	VF			1.6	V	IF=20mA
Reverse Current	IR			100	μA	VR=5V
Half Intensity Beam Angle	θHI		35		degree	IF=20mA
Peak Wavelength	λp		940		nm	IF=20mA
Spectrum Line Half Width	Δλ		45		nm	IF=20mA



MICRO ELECTRONICS LTD.
 38, Hung To Road, Microtron Buiding, Kwun Tong, Kowloon, Hong Kong.
 Kwun Tong P.O. Box 69477 Hong Kong. Fax No. 2341 0321 Telex:43510 Micro Hx. Tel: 2343 0181-5

MI 32T

