



Our commitment. Your advantage.

- [Products](#) [Documentation](#) [Resources](#) [My Account](#) [Customer Support](#)

[Home](#) > [Products](#) > [By Type](#) > [Passive Components](#) > [Product Feature Selector](#) > Product Details

3631B220LT Product Details



3631B220LT
(1-1625812-9)

TE Internal Number: 1-1625812-9

[Active](#)

Inductors

[Converted to EU RoHS/ELV Compliant \(Statement of Compliance\)](#)

Product Highlights:

- Inductor
- Inductor Type = Shielded Power Wirewound
- Lead Type = Surface Mount Terminals
- Wirewound
- Inductance = 22 ?H

[View all Features](#)

Quick Links

- [Check Pricing & Availability](#)
- [Search for Tooling](#)
- [Product Feature Selector](#)
- [Contact Us About This Product](#)

- [Add to My Part List](#) [Request Sample](#) [Find Similar Products](#) [Buy Product](#)

Documentation & Additional Information

Product Drawings:

- [SHIELDED SMD POWER INDUCTORS SERIES 3631](#) (PDF, English)

Catalog Pages/Data Sheets:

- [Shielded SMD Power Inductor - Type 3631 Series - Tyc...](#) (PDF, English)

Product Specifications:

- None Available

Application Specifications:

- None Available

Instruction Sheets:

- None Available

CAD Files:

- None Available

Additional Information:

- [Product Line Information](#)

Related Products:

- [Tooling](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Inductor
- Inductor Type = Shielded Power Wirewound
- [Element](#) = Wirewound
- [Shielded](#) = Yes

Electrical Characteristics:

- [Inductance \(?H\)](#) = 22
- [DC Resistance \(?\)](#) = 0.062
- [Current, Maximum \(mA\)](#) = 2300
- [Package Type](#) = Taped and Reeled
- Tolerance (%) = 15

Body Related Features:

- [Lead Type](#) = Surface Mount Terminals
- [Series](#) = 3631
- [Package, Component Size](#) = 12.7 x 12.7
- [Mount Style](#) = Surface Mount

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Reflow solder capable to 245?C, Reflow solder capable to 260?C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

Operation/Application:

- [Application](#) = High Power Circuitry

Other:

- Brand = Sigma Inductors

[Provide Website Feedback](#) | [Need Help?](#)