


**.300 Square Spade  
.040 Electro-Tinned Copper  
12-10 AWG (Yellow)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.207	.260	.300						
4	X			B	/	/	2500	50269	
		X		B	/	/	2000	50269-8	
			X	B	/	*	2000	50269-8A	
	X			W	/	/	2500	50270	
		X		W	/	/	2000	50270-8	
			X	W	/	*	2000	50270-8A	
6	X			B	/	/	2500	50281	
		X		B	/	/	2000	50281-8	
			X	B	/	*	2000	50281-8A	
	X			W	/	/	2500	50282	
		X		W	/	/	2000	50282-8	
			X	W	/	*	2000	50282-8A	
8	X			B	/	/	2500	50293	
		X		B	/	/	2000	50293-8	
			X	B	/	*	2000	50293-8A	
	X			W	/	/	2500	50294	
		X		W	/	/	2000	50294-8	
			X	W	/	*	2000	50294-8A	
10	X			B	/	/	2500	50305	
		X		B	/	/	2000	50305-8	
			X	B	/	*	2000	50305-8A	
	X			W	/	/	2500	50306	
		X		W	/	/	2000	50306-8	
			X	W	/	*	2000	50306-8A	



**S  
P  
A  
D  
E  
&  
R  
I  
N  
G**

Recommended Strip Length  $\frac{1}{16} \pm \frac{3}{64}$   
\* Contact Factory for Latest Agency Approvals