



注:
NOTE

1. 材料
MATERIAL
ピン：□0.635×14.2黄銅、銅下地錫めつき
PIN：□0.635×14.2 BRASS TIN OVER COPPER PLATING
ウエハー：ポリアミド、UL94V-0
WAFER: POLYAMIDE,UL94V-0
2. 6極以上に適応
TO BE APPLIED FOR 6 CKT. AND MORE THAN 6 CKT.
3. 5極以下はロック部スリットなし
NO SLIT IS PROVIDED FOR 5 CKT. AND LESS THAN 5 CKT.
4. ELV 及び RoHS 適合品
ELV AND RoHS COMPLIANT

1.35	0.85	35 ^{+0.3} / _{-0.45}	35	22 04 1151	15
↑	↑	32.5 ^{+0.25} / _{-0.45}	32.5	↑ 1141	14
		30 ^{+0.25} / _{-0.4}	30	1131	13
		27.5 ^{+0.25} / _{-0.4}	27.5	1121	12
		25 ^{+0.2} / _{-0.4}	25	1111	11
		22.5 ^{+0.2} / _{-0.4}	22.5	1101	10
		20 ^{+0.15} / _{-0.35}	20	1091	9
		17.5 ^{+0.15} / _{-0.35}	17.5	1081	8
		15 ^{+0.1} / _{-0.3}	15	1071	7
		12.5 ^{+0.1} / _{-0.3}	12.5	1061	6
↓	↓	10 ^{+0.15} / _{-0.3}	10	1051	5
1.35	0.85	7.5 ^{+0.15} / _{-0.3}	7.5	1041	4
1.2	1	5 ^{+0.15} / _{-0.3}	5	↓ 1031	3
1.2	1	2.5 ^{+0.15} / _{-0.3}	2.5	22 04 1021	2
D	E	C	B	ORDER No.	極数 CKT.

MODEL No. : 5045-**A

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

REVISED EC NO: 167225 DRWN: KYAMADA02 CHK'D: SAKIYAMA APPR: TKANEKO	2017/10/18	GENERAL TOLERANCES (UNLESS SPECIFIED) ANGULAR TOL ± 3.0 ° 4 PLACES ± 0.4 3 PLACES ± 0.4 2 PLACES ± 0.4 1 PLACE ± 0.4 0 PLACES ± 0.4 DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	DIMENSION UNITS	SCALE		
	2017/10/26		mm	5:1		
	2017/10/26		DRWN BY	DATE		KKOHAMA 2000/03/27
			CHK'D BY	DATE		KASAKAWA 2012/01/30
			APPR BY	DATE		
			NUKITA	2013/06/13		
			DRAWING SIZE	THIRD ANGLE PROJECTION		
			A3			
			PRODUCT CUSTOMER DRAWING			
			SERIES	MATERIAL NUMBER	CUSTOMER	
			5045	SEE CHART	GENERAL MARKET	
			DOCUMENT NUMBER	DOC TYPE	DOC PART SHEET NUMBER	
			SD-5045-NA	PSD	001 1 OF 1	