



**.380 Flanged Spade  
.040 Electro-Tinned Copper  
12-10 AWG (Yellow)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.207	.260	.300						
6	X			B	✓	✓	2500	50443	
		X		B	✓	✓	2000	50443-8	
			X	B	✓	*	2000	50443-8A	
	X			W	✓	✓	2500	50444	
		X		W	✓	✓	2000	50444-8	
			X	W	✓	*	2000	50444-8A	
8	X			B	✓	✓	2500	50455	
		X		B	✓	✓	2000	50455-8	
			X	B	✓	*	2000	50455-8A	
	X			W	✓	✓	2500	50456	
		X		W	✓	✓	2000	50456-8	
			X	W	✓	*	2000	50456-8A	
10	X			B	✓	✓	2500	50467	
		X		B	✓	✓	2000	50467-8	
			X	B	✓	*	2000	50467-8A	
	X			W	✓	✓	2500	50468	
		X		W	✓	✓	2000	50468-8	
			X	W	✓	*	2000	50468-8A	

**.500 Flanged Spade  
.040 Electro-Tinned Copper  
12-10 AWG (Yellow)**

**Spade and Ring Series  
Pre-Insulated**

STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER	STYLE AND DIMENSIONS
	.207	.260	.300						
10	X			B	✓	✓	2500	50656	
		X		B	✓	✓	2000	50656-8	
			X	B	✓	*	2000	50656-8A	
	X			W	✓	✓	2500	50657	
		X		W	✓	✓	2000	50657-8	
			X	W	✓	*	2000	50657-8A	
1/4	X			B	✓	✓	2500	50668	
		X		B	✓	✓	2000	50668-8	
			X	B	✓	*	2000	50668-8A	
	X			W	✓	✓	2500	50669	
		X		W	✓	✓	2000	50669-8	
			X	W	✓	*	2000	50669-8A	

Recommended Strip Length  $\frac{5}{16} \pm \frac{3}{64}$   
\* Contact Factory for Latest Agency Approvals

G  
N  
I  
R  
&  
E  
D  
A  
P  
S