

Photo-Triac Output

F7

Type No.	Pin Configuration	Features	IFT		V _{TM}		V _{ORM} (V)	BV _s (V _{rms})	Safety Standard (Note 2)			
			Rank	MAX. (mA)	Max. (V)	@ I _{TM} (mA)			UL	TÜV	VDE	BSI
TLP3021		Direct replacement for XXX3021	—	15								
TLP3022		Direct replacement for XXX3022	—	10	3.0	100	400	5,000	○	△ VDE 0884	○ VDE 0884 Option (D4)	△ 415
TLP3023		Direct replacement for XXX3023	—	5								
TLP3041		Direct replacement for XXX3041	—	15								
TLP3042		Direct replacement for XXX3042	—	10	3.0	100	400	5,000	○	△ VDE 0884	○ VDE 0884 Option (D4)	△ 415
TLP3043		Direct replacement for XXX3043	—	5								
TLP3051		High V _{ORM} Non-zero-voltage turn-on	—	15	3.0	100	600	5,000	○	△ VDE 0884	○ VDE 0884 Option (D4)	△ 415
TLP3052		Low IFT	—	10								
TLP3061		Direct replacement for XXX3060/3061	—	15								
TLP3062		Direct replacement for XXX3062	—	10	3.0	100	600	5,000	○	△ VDE 0884	○ VDE 0884 Option (D4)	△ 415
TLP3063		Direct replacement for XXX3063	—	5								
TLP3064		Extra Low IFT	—	3					○	△ VDE 0884	△ VDE 0884	△ 415