Raychem

TE Internal #: 216327-000

Hook Up Wire, MIL-DTL-22759, 600V Voltage Rating, Red Wire Color, 28AWG Wire Size, Operating Temperature Range -65 - 150 $^{\circ}$

View on TE.com >



Wire & Cable > Hook Up Wire



Cable Type: MIL-DTL-22759

Voltage Rating: 600 V

Wire Color: Red

Insulation Material: Modified Radiation Cross-linked ETFE Polymer

Conductor Material: Tin-Coated Copper

Features

Product Type Features

Cable Style	Primary
Product Type	Cable
Product Classification	Cable - High Performance - Spec 44, 55 & RCW
Cable Type	MIL-DTL-22759
Configuration Features	

Configuration Features

Number of Conductors	1
Number of Strands	7

Electrical Characteristics

Body Features

Wire Color	Red
Insulation Material	Modified Radiation Cross-linked ETFE Polymer
Conductor Material	Tin-Coated Copper

Dimensions

Overall Outside Diameter	.69 mm[.027 in]
Wire Diameter	.69 mm[.027 in]



Conductor Diameter	.38 mm[.015 in]
	.005 in
Strand Size	36 AWG
Wire Size	28 AWG
Usage Conditions	
Operating Temperature Range	-65 – 150 °C
Other	
Wire Source	United States

Product Compliance

For compliance documentation, visit the product page on TE.com>


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUN 2020 (209) Candidate List Declared Against: JUL 2019 (201) Does not contain REACH SVHC
Halogen Content	Out of Scope - excluded from Halogen requirements
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts






Customers Also Bought



TE Model / Part #990207-000 TXR40AB00-1408BI




TE Model / Part #216389-000 22759/32-28-6









TE Model / Part #1057699-1 3106 7985 00



TE Model / Part #1059928-1 ADAPTER, OSSP JACK TO SMA JACK



TE Model / Part #216326-000 22759/32-28-0



TE Model / Part #480857-000 22759/32-28-3



TE Model / Part #DTS24F23-55PN RECP ASSY



Documents

Product Drawings 22759/32-28-2

English

Datasheets & Catalog Pages

1654025_Sec9_SPEC55

English

Raychem Wire and Cable Quick Reference Guide

English

Hook Up Wire, MIL-DTL-22759, 600V Voltage Rating, Red Wire Color, 28AWG Wire Size, Operating Temperature Range -65 – 150 °C



Product Specifications
Product Specification

English