

DDR4 SDRAM UDIMM

Addendum

MTA16ATF4G64AZ – 32GB


Introduction

Information provided here is in addition to or supersedes information provided in the Micron DDR4 UDIMM Core data sheet.

Features

- DDR4 functionality and operations supported as defined in the component data sheet
- Features and specifications supported in the Micron DDR4 UDIMM core data sheet
- 288-pin, unbuffered dual in-line memory module (UDIMM)
- Fast data transfer rates: PC4-3200, PC4-2666
- 32GB (4 Gig x 64)
- Data bus inversion (DBI) for data bus
- On-board serial presence-detect (SPD) EEPROM
- Dual-rank
- 16 internal banks; 4 groups of 4 banks each

Figure 1: 288-Pin UDIMM (R/C-B2)



Options

- Operating temperature
 - Commercial (0°C ≤ T_{OPER} ≤ 95°C)
- Package
 - 288-pin DIMM (halogen-free)
- Frequency/CAS latency
 - 0.625ns @ CL = 22 (DDR4-3200)
 - 0.75ns @ CL = 19 (DDR4-2666)

Marking

None
Z
-3G2
-2G6

Table 1: Addressing

Parameter	32GB
Row address	128K A[16:0]
Column address	1K A[9:0]
Device bank group address	4 BG[1:0]
Device bank address per group	4 BA[1:0]
Device configuration	16Gb (2 Gig x 8), 16 banks
Module rank address	2 CS _n [1:0]

Table 2: Part Numbers and Timing Parameters – 32GB Modules

Base device: MT40A2G8,¹ 16Gb DDR4 SDRAM

Part Number ²	Module Density	Configuration	Module Bandwidth	Memory Clock/ Data Rate	Clock Cycles (CL _{-n} RCD _{-n} RP)
MTA16ATF4G64AZ-3G2__	32GB	4 Gig x 64	25.6 GB/s	0.625ns/3200 MT/s	22-22-22
MTA16ATF4G64AZ-2G6__	32GB	4 Gig x 64	21.3 GB/s	0.75ns/2666 MT/s	19-19-19

- Notes:
1. The data sheet for the base device can be found on micron.com.
 2. All part numbers end with a two-place code (not shown) that designates component and PCB revisions. Consult factory for current revision codes. Example: MTA16ATF4G64AZ-3G2B1.

Important Notes and Warnings

Micron Technology, Inc. ("Micron") reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions. This document supersedes and replaces all information supplied prior to the publication hereof. You may not rely on any information set forth in this document if you obtain the product described herein from any unauthorized distributor or other source not authorized by Micron.

Automotive Applications. Products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets. Distributor and customer/distributor shall assume the sole risk and liability for and shall indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting directly or indirectly from any use of non-automotive-grade products in automotive applications. Customer/distributor shall ensure that the terms and conditions of sale between customer/distributor and any customer of distributor/customer (1) state that Micron products are not designed or intended for use in automotive applications unless specifically designated by Micron as automotive-grade by their respective data sheets and (2) require such customer of distributor/customer to indemnify and hold Micron harmless against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, death, or property damage resulting from any use of non-automotive-grade products in automotive applications.

Critical Applications. Products are not authorized for use in applications in which failure of the Micron component could result, directly or indirectly in death, personal injury, or severe property or environmental damage ("Critical Applications"). Customer must protect against death, personal injury, and severe property and environmental damage by incorporating safety design measures into customer's applications to ensure that failure of the Micron component will not result in such harms. Should customer or distributor purchase, use, or sell any Micron component for any critical application, customer and distributor shall indemnify and hold harmless Micron and its subsidiaries, subcontractors, and affiliates and the directors, officers, and employees of each against all claims, costs, damages, and expenses and reasonable attorneys' fees arising out of, directly or indirectly, any claim of product liability, personal injury, or death arising in any way out of such critical application, whether or not Micron or its subsidiaries, subcontractors, or affiliates were negligent in the design, manufacture, or warning of the Micron product.

Customer Responsibility. Customers are responsible for the design, manufacture, and operation of their systems, applications, and products using Micron products. ALL SEMICONDUCTOR PRODUCTS HAVE INHERENT FAILURE RATES AND LIMITED USEFUL LIVES. IT IS THE CUSTOMER'S SOLE RESPONSIBILITY TO DETERMINE WHETHER THE MICRON PRODUCT IS SUITABLE AND FIT FOR THE CUSTOMER'S SYSTEM, APPLICATION, OR PRODUCT. Customers must ensure that adequate design, manufacturing, and operating safeguards are included in customer's applications and products to eliminate the risk that personal injury, death, or severe property or environmental damages will result from failure of any semiconductor component.

Limited Warranty. In no event shall Micron be liable for any indirect, incidental, punitive, special or consequential damages (including without limitation lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort, warranty, breach of contract or other legal theory, unless explicitly stated in a written agreement executed by Micron's duly authorized representative.



DQ Map

Table 3: Component-to-Module DQ Map

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U1	0	2	12	U2	0	11	168
	1	1	150		1	9	161
	2	3	157		2	10	23
	3	0	5		3	8	16
	4	6	10		4	15	166
	5	4	3		5	13	159
	6	7	155		6	14	21
	7	5	148		7	12	14
U3	0	18	34	U4	0	27	190
	1	16	27		1	24	38
	2	19	179		2	26	45
	3	17	172		3	25	183
	4	22	32		4	31	188
	5	20	25		5	29	181
	6	23	177		6	30	43
	7	21	170		7	28	36
U6	0	38	102	U7	0	47	258
	1	37	240		1	44	106
	2	39	247		2	46	113
	3	36	95		3	45	251
	4	35	249		4	42	115
	5	33	242		5	40	108
	6	34	104		6	43	260
	7	32	97		7	41	253
U8	0	55	269	U9	0	63	280
	1	53	262		1	60	128
	2	54	124		2	62	135
	3	52	117		3	61	273
	4	51	271		4	58	137
	5	48	119		5	56	130
	6	50	126		6	59	260
	7	47	264		7	57	275



Table 3: Component-to-Module DQ Map (Continued)

Component Reference Number	Component DQ	Module DQ	Module Pin Number	Component Reference Number	Component DQ	Module DQ	Module Pin Number
U10	0	60	128	U11	0	53	262
	1	63	280		1	55	269
	2	61	273		2	52	117
	3	62	135		3	54	124
	4	56	130		4	48	119
	5	58	137		5	51	271
	6	57	275		6	49	264
	7	59	282		7	50	126
U12	0	44	106	U13	0	37	240
	1	47	258		1	38	102
	2	45	251		2	36	95
	3	46	113		3	39	247
	4	40	108		4	33	242
	5	42	115		5	35	249
	6	41	253		6	32	97
	7	43	260		7	34	104
U14	0	24	38	U15	0	16	27
	1	27	190		1	18	34
	2	25	183		2	17	172
	3	26	45		3	19	179
	4	29	181		4	20	25
	5	31	188		5	22	32
	6	28	36		6	21	170
	7	30	43		7	23	177
U16	0	9	161	U17	0	1	150
	1	11	168		1	2	12
	2	8	16		2	0	5
	3	10	23		3	3	157
	4	13	159		4	4	3
	5	15	166		5	6	10
	6	12	14		6	5	148
	7	14	21		7	7	155

I_{DD} Specifications

Table 4: DDR4 I_{DD} Specifications and Conditions (0° ≤ T_C ≤ 85°) – 32GB (Die Revision E)

Values are for the MT40A2GM8 DDR4 SDRAM only and are computed from values specified in the 16Gb (2 Gig x 8) component data sheet

Parameter	Symbol	3200	2666	Units
One bank ACTIVATE-PRECHARGE current	I _{DD0} ¹	784	768	mA
One bank ACTIVATE-PRECHARGE, wordline boost, I _{pp} current	I _{PP0} ¹	40	40	mA
One bank ACTIVATE-READ-PRECHARGE current	I _{DD1} ¹	872	856	mA
Precharge standby current	I _{DD2N} ²	720	688	mA
Precharge standby ODT current	I _{DD2NT} ¹	712	696	mA
Precharge power-down current	I _{DD2P} ²	608	608	mA
Precharge quiet standby current	I _{DD2Q} ²	672	672	mA
Active standby current	I _{DD3N} ²	976	944	mA
Active standby I _{pp} current	I _{PP3N} ²	32	32	mA
Active power-down current	I _{DD3P} ²	800	768	mA
Burst read current	I _{DD4R} ¹	1600	1472	mA
Burst write current	I _{DD4W} ¹	1328	1240	mA
Different logic rank burst refresh current (1x REF)	I _{DD5R} ¹	848	848	mA
Different logic rank burst refresh I _{pp} current (1x REF)	I _{PP5R} ¹	48	48	mA
Self refresh current: Normal temperature range (0°C to 85°C)	I _{DD6N (0–85°C)} ²	848	848	mA
Self refresh current: Extended temperature range (0°C to 95°C)	I _{DD6E (0–95°C)} ²	1808	1808	mA
Self refresh current: Reduced temperature range (0°C to 45°C)	I _{DD6R (0–45°C)} ²	320	320	mA
Auto self refresh current (25°C)	I _{DD6A (25°C)} ²	176	176	mA
Auto self refresh current (45°C)	I _{DD6A (45°C)} ²	320	320	mA
Auto self refresh current (75°C)	I _{DD6A (75°C)} ²	816	816	mA
Auto self refresh current (95°C)	I _{DD6A (95°C)} ²	1808	1808	mA
Auto self refresh I _{pp} current (0°C to 95°C)	I _{PP6X} ²	96	96	mA
Bank interleave read current	I _{DD7} ¹	1784	1752	mA
Bank interleave read I _{pp} current	I _{PP7} ¹	128	128	mA
Maximum power-down current	I _{DD8} ²	576	576	mA

- Notes:
1. One module rank in the active I_{DD}/I_{pp}, the other rank in I_{DD2P}/I_{PP3N}.
 2. All ranks in this I_{DD}/I_{pp} condition.
 3. When T_C > 85°C, the I_{DD} and I_{pp} values must be derated. Refer to the base device data sheet I_{DD} and I_{pp} specification tables for derating values for the applicable die-revision.

Table 5: DDR4 I_{DD} Specifications and Conditions (0° ≤ T_C ≤ 85°) – 32GB (Die Revision B)

Values are for the MT40A2GM8 DDR4 SDRAM only and are computed from values specified in the 16Gb (2 Gig x 8) component data sheet

Parameter	Symbol	3200	2666	Units
One bank ACTIVATE-PRECHARGE current	I _{DD0} ¹	848	832	mA
One bank ACTIVATE-PRECHARGE, wordline boost, I _{PP} current	I _{PP0} ¹	56	56	mA
One bank ACTIVATE-READ-PRECHARGE current	I _{DD1} ¹	936	920	mA
Precharge standby current	I _{DD2N} ²	832	800	mA
Precharge standby ODT current	I _{DD2NT} ¹	792	776	mA
Precharge power-down current	I _{DD2P} ²	688	688	mA
Precharge quite standby current	I _{DD2Q} ²	752	752	mA
Active standby current	I _{DD3N} ²	1280	1248	mA
Active standby I _{PP} current	I _{PP3N} ²	48	48	mA
Active power-down current	I _{DD3P} ²	1104	1088	mA
Burst read current	I _{DD4R} ¹	1960	1800	mA
Burst write current	I _{DD4W} ¹	1808	1672	mA
Different logic rank burst refresh current (1x REF)	I _{DD5R} ¹	976	960	mA
Different logic rank burst refresh I _{PP} current (1x REF)	I _{PP5R} ¹	64	64	mA
Self refresh current: Normal temperature range (0°C to 85°C)	I _{DD6N} (0–85°C) ²	1072	1072	mA
Self refresh current: Extended temperature range (0°C to 95°C)	I _{DD6E} (0–95°C) ²	1936	1936	mA
Self refresh current: Reduced temperature range (0°C to 45°C)	I _{DD6R} (0–45°C) ²	464	464	mA
Auto self refresh current (25°C)	I _{DD6A} (25°C) ²	160	160	mA
Auto self refresh current (45°C)	I _{DD6A} (45°C) ²	464	464	mA
Auto self refresh current (75°C)	I _{DD6A} (75°C) ²	976	976	mA
Auto self refresh current (95°C)	I _{DD6A} (95°C) ²	1936	1936	mA
Auto self refresh I _{PP} current (0°C to 95°C)	I _{PP6X} ²	176	176	mA
Bank interleave read current	I _{DD7} ¹	1912	1864	mA
Bank interleave read I _{PP} current	I _{PP7} ¹	104	104	mA
Maximum power-down current	I _{DD8} ²	640	640	mA

- Notes:
1. One module rank in the active I_{DD}/I_{PP}, the other rank in I_{DD2P}/I_{PP3N}.
 2. All ranks in this I_{DD}/I_{PP} condition.
 3. When T_C > 85°C, the I_{DD} and I_{PP} values must be derated. Refer to the base device data sheet I_{DD} and I_{PP} specification tables for derating values for the applicable die-revision.



32GB (x64, DR) 288-Pin DDR4 UDIMM Functional Block Diagram

8000 S. Federal Way, P.O. Box 6, Boise, ID 83707-0006, Tel: 208-368-4000
www.micron.com/products/support Sales inquiries: 800-932-4992
Micron and the Micron logo are trademarks of Micron Technology, Inc.
All other trademarks are the property of their respective owners.

This data sheet contains minimum and maximum limits specified over the power supply and temperature range set forth herein.
Although considered final, these specifications are subject to change, as further product development and data characterization some-
times occur.