



DC OPERATED - SOLDER TERMINAL or PLUG-IN STYLE						
STANDARD CONTACTS		COIL Measured @ 25°C			CONTACT CONFIGURATION	CROSS REFERENCE TO POTTER & BRUMFIELD
PART NUMBERS	CONTACT RATING	NOMINAL INPUT VOLTAGE	NOMINAL RESISTANCE (OHMS)	NOMINAL POWER (WATTS)		
W67RCSX-1	5 AMPS	5	52	1/2W	DPDT	R10E1X2-28V
W67RCSX-2	5 AMPS	12	185	3/4W	DPDT	R10E1X2-185V
W67RCSX-3	5 AMPS	24	700	1W	DPDT	R10E1X2-700V
W67RCSX-4	5 AMPS	48	2500	1W	DPDT	R10E1X2-2.5KV
W67RCSX-5	5 AMPS	115	15,000	1W	DPDT	R10E1X2-15.0KV
W67RCSX-6	5 AMPS	5	52	1/2W	4PDT	R10E1X4-28V
W67RCSX-7	5 AMPS	12	185	3/4W	4PDT	R10E1X4-185V
W67RCSX-8	5 AMPS	24	700	1W	4PDT	R10E1X4-700V
W67RCSX-9	5 AMPS	48	2500	1W	4PDT	R10E1X4-2.5KV
W67RCSX-10	5 AMPS	115	15,000	1W	4PDT	R10E1X4-15.0KV
W67RCSX-12	5 AMPS	12	90	1.5W	6PDT	R10E1X6-185V
W67RCSX-13	5 AMPS	24	430	1.5W	6PDT	R10E1X6-700V
W67RCSX-17	5 AMPS	12	72	2W	8PDT	R10E1X8-185V
W67RCSX-18	5 AMPS	24	350	2W	8PDT	R10E1X8-700V

DC OPERATED - BIFURCATED CONTACTS - FOR LOW LEVEL SWITCHING APPLICATIONS						
PART NUMBERS	CONTACT RATING	NOMINAL INPUT VOLTAGE	NOMINAL RESISTANCE (OHMS)	NOMINAL POWER (WATTS)	CONTACT CONFIGURATION	CROSS REFERENCE TO POTTER & BRUMFIELD
W67TRCSX-2	3 AMPS	12	185	3/4W	DPDT	R10E1P2-185V
W67TRCSX-3	3 AMPS	24	700	1W	DPDT	R10E1P2-700V
W67TRCSX-7	3 AMPS	12	185	3/4W	4PDT	R10E1P4-185V
W67TRCSX-8	3 AMPS	24	700	1W	4PDT	R10E1P4-700V
W67TRCSX-12	3 AMPS	12	90	1.5W	6PDT	R10E1P6-185V
W67TRCSX-13	3 AMPS	24	430	1.5W	6PDT	R10E1P6-700V
W67TRCSX-17	3 AMPS	12	72	2W	8PDT	R10E1P8-185V
W67TRCSX-18	3 AMPS	24	350	2W	8PDT	R10E1P8-700V

CLASS 67 - AC OPERATED RELAYS - SOLDER TERMINAL or PLUG-IN STYLE 50/60 Hz						
STANDARD CONTACTS		COIL Measured @ 25°C			CONTACT CONFIGURATION	CROSS REFERENCE TO POTTER & BRUMFIELD
PART NUMBERS	CONTACT RATING	NOMINAL INPUT VOLTAGE	NOMINAL RESISTANCE (OHMS)	NOMINAL POWER (WATTS)		
W67ARCSX-5	5 AMPS	120 VAC	-	1.5VA	DPDT	R10E1X2-120V
W67ARCSX-10	5 AMPS	120 VAC	-	2.5VA	4PDT	R10E1X4-120V
W67ARCSX-15	5 AMPS	120 VAC	-	2.5VA	6PDT	R10E1X6-120V

CLASS 67 - DC OPERATED - ULTRA SENSITIVE - SOLDER TERMINAL or PLUG-IN STYLE							
STANDARD CONTACTS		COIL Measured @ 25°C				CONTACT CONFIGURATION	CROSS REFERENCE TO POTTER & BRUMFIELD
PART NUMBERS	CONTACT RATING	NOMINAL INPUT MILLIAMPS DC	NOMINAL RESISTANCE (OHMS)	PULL-IN MILLIAMPS DC	PULL-IN WATTS		
W67SCSX-1	3 AMPS	9.4 mADC	1000	9.2 mADC	85mW	DPDT	R10SE1X2-1.0K
W67SCSX-2	3 AMPS	6.4 mADC	2500	6.3 mADC	100mW	DPDT	R10SE1X2-2.5K
W67SCSX-3	3 AMPS	4.5 mADC	5000	4.4 mADC	100mW	DPDT	R10SE1X2-5.0K
W67SCSX-6	3 AMPS	13.7 mADC	1000	13.5 mADC	200mW	4PDT	R10SE1X4-1.0K
W67SCSX-7	3 AMPS	9.1 mADC	2500	8.9 mADC	200mW	4PDT	R10SE1X4-2.5K
W67SCSX-8	3 AMPS	6.5 mADC	5000	6.3 mADC	200mW	4PDT	R10SE1X4-5.0K

Part numbers shown also available thru Stocking Distribution.