

ROTARY SWITCHES

MRS, MRSE, MRSB and MRBA

HOW TO ORDER INFORMATION

HOW TO ORDER

MR**SERIES**
S, SE, SB, BA

NO. OF POLES	MAX NO. OF POSITIONS	
1	10 (36° EACH)	12 (30° EACH)
2	5	6
3	3	4

OPTIONS

C = CONTINUOUS ROTATION
 S = .72" SHAFT LENGTH (EXCEPT MRSB)
 CONSULT FACTORY FOR CUSTOM SHAFTS
 BLANK = .29" STANDARD SHAFT LENGTH
 WITH ADJUSTABLE STOPS (EXCEPT MRSB)
 CS = CONTINUOUS ROTATION &
 .72" SHAFT LENGTH (EXCEPT MRSB)
 CONSULT FACTORY FOR CUSTOM SHAFTS

KNOBS (MRSB ONLY)

K = MRSB WITH .50" DIAMETER KNOB ATTACHED
 U = MRSB WITH .58" SKIRTED KNOB ATTACHED

CONTACTS

BLANK = SILVER
 G = GOLD

CONTACT TIMING

BLANK = NON-SHORTING
 X = SHORTING

TERMINALS

BLANK = WIRE LUG
 PC = PRINTED CIRCUIT BOARD TERMINALS
 RA = RIGHT ANGLE PC

EXAMPLE: MRS2 6CSGXPC = MRS SERIES
 2 POLE
 6 POSITION
 CONTINUOUS ROTATION
 .72" LONG SHAFT
 GOLD CONTACTS
 SHORTING
 P.C. TERMINATION

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE.