



MYRRA - SERIE 45000 UI 39 10 VA - 30 VA

CIRCUIT	RATING	DIMENSION A	WEIGHT
UI 39 x 8	10 VA	A = 22 mm	285 g
UI 39 x 10,2	14 VA	A = 24 mm	335 g
UI 39 x 13,5	18 VA	A = 27 mm	405 g
UI 39 x 17	24 VA	A = 31 mm	480 g
UI 39 x 21	30 VA	A = 35 mm	550 g

Possible primary connections

Possible secondary connections

Primary voltage 115 V - 230 V  
UI 39 x 8 10 VA

Protection	Reference	Secondary Voltage V	Secondary Current mA	No-load Voltage V	Ambient, Temperature C
125/63	45037	2 x 6	2 x 833	2 x 8,2	T 50 B
125/63	45038	2 x 9	2 x 555	2 x 12,3	T 50 B
125/63	45039	2 x 12	2 x 416	2 x 16,4	T 50 B
125/63	45040	2 x 15	2 x 333	2 x 20,5	T 50 B

125/63	45041	2 x 18	2 x 277	2 x 24,6	T 50 B
125/63	45042	2 x 24	2 x 208	2 x 32,8	T 50 B

Primary voltage 115 V - 230 V  
UI 39 x 10,2 14 VA

Protection	Reference	Secondary Voltage V	Secondary Currant mA	No-load Voltage V	Ambient, Temperature C
160/80	45043	2 x 6	2 x 1167	2 x 7,5	T 50 B
160/80	45044	2 x 9	2 x 778	2 x 10,9	T 50 B
160/80	45045	2 x 12	2 x 583	2 x 15,0	T 50 B
160/80	45046	2 x 15	2 x 467	2 x 18,7	T 50 B
160/80	45047	2 x 18	2 x 389	2 x 22,4	T 50 B
160/80	45048	2 x 24	2 x 292	2 x 30,2	T 50 B

Primary voltage 115 V - 230 V  
UI 39 x 13,5 second protection mA 18 VA

Protection	Reference	Secondary Voltage V	Secondary Currant mA	No-load Voltage V	Ambient, Temperature C
200/100	45049	2 x 6	2 x 1500	2 x 7,4	T 50 B
200/100	45050	2 x 9	2 x 1000	2 x 11,0	T 50 B
200/100	45051	2 x 12	2 x 750	2 x 14,7	T 50 B
200/100	45052	2 x 15	2 x 600	2 x 18,3	T 50 B
200/100	45053	2 x 18	2 x 500	2 x 22,0	T 50 B
200/100	45054	2 x 24	2 x 375	2 x 29,4	T 50 B

Primary voltage 115 V - 230 V  
UI 39 x 17 24 VA

Protection	Reference	Secondary Voltage V	Secondary Currant mA	No-load Voltage V	Ambient, Temperature C
250/150	45055	2 x 6	2 x 2000	2 x 7,1	T 50 B
250/125	45056	2 x 9	2 x 1333	2 x 10,6	T 50 B
250/125	45057	2 x 12	2 x 1000	2 x 14,1	T 50 B
250/125	45058	2 x 15	2 x 800	2 x 17,6	T 50 B
250/125	45059	2 x 18	2 x 667	2 x 21,2	T 50 B
125	45060	2 x 24	2 x 500	2 x 28,3	T 50 B

Primary voltage 115 V - 230 V  
UI 39 x 21 30 VA

Protection	Reference	Secondary Voltage V	Secondary Currant mA	No-load Voltage V	Ambient, Temperature C
------------	-----------	---------------------	----------------------	-------------------	------------------------

315/160	45061	2 x 6	2 x 2500	2 x 6,7	T 50 B
315/160	45062	2 x 9	2 x 1667	2 x 10,15	T 50 B
315/160	45063	2 x 12	2 x 1250	2 x 13,5	T 50 B
315/160	45064	2 x 1000	2 x 16,8	2 x 19,8	T 50 B
315/160	45065	2 x 18	2 x 833	2 x 20,2	T 50 B
315/160	45066	2 x 24	2 x 625	2 x 27,0	T 50 B

- 115 V - 230 V supply voltage by series/parallel connection
- Vacuum filling
- Two compartments bobbins
- Degree of protection IP 00
- Resin UL 94 VO
- Fuse protection in secondary winding (see diagram)
- Insulation voltage 4KV (6 KV MYRRA test)
- 100 % tested production
- Conform to EN 60742
- Approval under process
- UL 506 approved