






Verpackt in Gurtverpackung
 Tape on Reel Packaging
 Verpackungseinheit: 440 Stück
 Packaging unit: 440 pcs



Leiterplatten-Layout Vorschlag für SMT
 PCB-Layout Proposal for SMT




Anforderungsstufe 1
 Performance Level 1

Kontaktbereich vergoldet
 Mating Area gold plating

Anschlussbereich verzinkt 4-6 µm
 Terminal Area 4-6 µm tin plating

Koplanarität der Anschlüsse ≤ 0,1 mm
 Coplanarity Area of Termination ≤ 0,1 mm



454195		weiß white	0,6	6,6	1,2	6,0	Codierung wie Variante schwarz Encoding such variant black
254702		rot red	4,2	3,0	4,8	2,4	
254701		grün green	3,0	4,2	3,6	3,6	
254700		blau blue	1,8	5,4	2,4	4,8	
254699		schwarz black	0,6	6,6	1,2	6,0	
Ident-Nr. part-no.	Codierung coding	Farbe color	A	B	C	D	Bemerkung note

Information:		Tolerances		Scale	3:1
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.		Subject to modification without prior notice. Drawing will not be updated.		Designation M 2.54 SRC-A, 6-polig	
e	15.04.2013	ERNI www.ERNI.com		224913	
Index	Date	Class		SRCA	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[254699](#) [254702](#) [254700](#) [254701](#) [254699-E](#) [254700-E](#) [254701-E](#) [254702-E](#)