


REVISIONS	
ISSUE	CHANGES
0	ER 36109 KH 02/16/95
B	REVISED PER DMF304 & ER 35722 KPL 11/4/11
CUSTOMER SALES DRAWING	
THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.	
SCALE	4:1
APPROX SURFACE AREA	
CAGE CODE:	91836
REF:	BOEING
JACK, PANEL, C	
DRAWN	KH
DATE	02/16/95
DESIGN	JT
DATE	02/17/95
APPR.	
 Winchester Electronics Corporation 62 Barnes Industrial Road North Wallingford, Connecticut 06492	
791-11-9	

NOTES:

1. FOR USE WITH BOEING BMS13-65 OK & ADAMS RUSSELL FC48Z CABLE.
2. FOR CABLING INSTRUCTIONS SEE 3-546-2.
3. FOR CRIMPING USE DIE KTH-2229.
4. INTERFACE PER MIL-STD-348, FIG. 302-2.
5. FOR USE WITH .26 MAX PANEL.
6. CENTER CONTACT (1-7214-2MA9) SUPPLIED UNASSEMBLED.
7. MARK PACKAGE: KINGS 791-11-9 (DATE CODE)
8. MATERIALS:  
 INSULATOR-TEFLON, ASTM D1710  
 K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM B135  
 CENTER CONTACT-BER. COP., ASTM B196  
 ALL OTHER METAL PARTS-BRASS, ASTM B16

9. FINISHES:  
 CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM B488 OVER  
 .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)  
 ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290  
 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
10. ELECTRICAL CHARACTERISTICS:  
 NOMINAL IMPEDANCE-50 OHMS  
 FREQUENCY RANGE-DC TO 11 GHZ  
 WORKING VOLTAGE-1000 VRMS
11. WEIGHT: 39.2 GRAMS

791-11-9