


Spade and Ring Series

Pre-Insulated

.380 Square Spade
.040 Electro-Tinned Copper
12-10 AWG (Yellow)


S P A D E & R I N G

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER		
		.207	.260	.300							
	6	X			B	✓	✓	2500	50491		
				X		B	✓	✓	2000	50491-8	
						X	B	✓	*	2000	50491-8A
		X				W	✓	✓	2500	50492	
					X		W	✓	✓	2000	50492-8
						X	W	✓	*	2000	50492-8A
	8	X				B	✓	✓	2500	50503	
				X		B	✓	✓	2000	50503-8	
					X	B	✓	*	2000	50503-8A	
		X				W	✓	✓	2500	50504	
					X		W	✓	✓	2000	50504-8
						X	W	✓	*	2000	50504-8A
10	X				B	✓	✓	2500	50515		
			X		B	✓	✓	2000	50515-8		
				X	B	✓	*	2000	50515-8A		
	X				W	✓	✓	2500	50516		
				X		W	✓	✓	2000	50516-8	
					X	W	✓	*	2000	50516-8A	

Spade and Ring Series

Pre-Insulated

.500 Square Spade
.040 Electro-Tinned Copper
12-10 AWG (Yellow)

STYLE AND DIMENSIONS	STUD	MAX. INSULATION DIAMETER			SEAM	UL	CSA	QUANTITY PER REEL	PART NUMBER		
		.207	.260	.300							
	10	X			B	✓	✓	2500	50695		
				X		B	✓	✓	2000	50695-8	
						X	B	✓	*	2000	50695-8A
		X				W	✓	✓	2500	50696	
					X		W	✓	✓	2000	50696-8
						X	W	✓	*	2000	50696-8A
	1/4	X				B	✓	✓	2500	50707	
				X		B	✓	✓	2000	50707-8	
					X	B	✓	*	2000	50707-8A	
		X				W	✓	✓	2000	50708-8	
					X		W	✓	✓	2000	50708-8
						X	W	✓	*	2000	50708-8A

Recommended Strip Length $\frac{5}{16} \pm \frac{3}{64}$
* Contact Factory for Latest Agency Approvals