




FEATURES AND SPECIFICATIONS



Wire Range	Material: Brass or Steel			Krimptite®			Insulkrimp®		
	Stud Size S	Max. Width W	Min. Clearance C	Order No.	Mylar Tape Order No.	Max. Length L	Order No.	Mylar Tape Order No.	Max. Length L
22-18 0.3-1.0mm ²	3-4 (2,6)	.197 (5,0)	.178 (4,5)				19121-0002	19121-0003	.727 (18.5)
	5-6 (3-3,5)	.301 (7,6)	.207 (5,3)	19118-0021	19118-0022	.556 (14.1)	19121-0005	19121-0006	.781 (19.8)
		.335 (8,5)	.235 (6,0)	19118-0038	19118-0109	.640 (16.2)	19121-0022	19121-0023	.865 (21.9)
	8 (4)	.301 (7,6)	.207 (5,3)	19118-0023	19118-0024	.556 (14.1)	19121-0007	19121-0008	.781 (19.8)
	10 (-)	.301 (7,6)	.207 (5,3)	19118-0025	19118-0099	.556 (14.1)	19121-0009	19121-0010	.781 (19.8)
16-14 1.2-2.0mm ²	5-6 (3-3,5)	.301 (7,6)	.209 (5,3)	19118-0054	19118-0055	.570 (14.4)	19121-0026	19121-0027	.795 (20.2)
	8 (4)	.301 (7,6)	.209 (5,3)	19118-0056	19118-0057	.570 (14.4)	19121-0028	19121-0029	.795 (20.2)
	10 (-)	.301 (7,6)	.209 (5,3)	19118-0058	19118-0059	.570 (14.4)	19121-0030	19121-0031	.795 (20.2)
		.385 (9,8)	.235 (6,0)	19118-0068	19118-0069	.633 (16.1)	19121-0040	19121-0041	.858 (21.8)
	5-6 (3-3,5)	.330 (8,4)	.305 (7,8)				19121-0046	19121-0085	1.075 (27.3)
12-10 3.0-6.0mm ²		.385 (9,8)	.301 (7,7)				19121-0051	19121-0052	1.061 (27.0)
	8 (4)	.330 (8,4)	.305 (7,8)	19118-0080	19118-0081	.784 (19.9)	19121-0047	19121-0048	1.075 (27.3)
		.385 (9,8)	.301 (7,7)	19118-0086	19118-0087	.770 (19.6)	19121-0053	19121-0054	1.061 (27.0)
		.425 (10,8)	.305 (7,8)				19121-0045	19121-0084	1.075 (27.3)
	10 (-)	.330 (8,4)	.305 (7,8)	19118-0082	19118-0083	.784 (19.9)	19121-0049	19121-0050	1.075 (27.3)
		.385 (9,8)	.301 (7,7)	19118-0088	19118-0090	.770 (19.6)	19121-0056	19121-0057	1.061 (27.0)

Product Specifications

Wire Range	Barrel Length	Material Thickness Max.	Insulation Color	Max. Wire Insulation Dia.		Circular Mil Area
				Insulkrimp®	Avikrimp®	
22-18 AWG	.175 (4,4)	.032 (0,8)	Red	.145 (3,7)	.140 (3,6)	509-2,600
16-14 AWG	.175 (4,4)	.032 (0,8)	Blue	.175 (4,4)	.170 (4,3)	2,050-5,180
12-10 AWG	.250 (6,4)	.040 (1,0)	Yellow	.250 (6,4)	.225 (5,7)	5,180-13,100