

M2001 Series

5x7 mm, 3.3 Volt, CMOS/LVPECL/LVDS, Clock Oscillator



- Low cost oscillator series with jitter performance optimized specifically for Fibre Channel applications. CMOS, LVPECL, and LVDS versions available.
- Ideal for Fibre Channel, Storage Area Networks (SAN), and HDD Control

Ordering Information		M2001		1	5	T	L	N	00.0000 MHz
Product Series									
Temperature Range									
1: 0°C to +70°C									
2: -40°C to +85°C									
6: -20°C to +70°C									
7: -0°C to +85°C									
8: 0°C to +50°C									
Stability									
3: ±100 ppm									
4: ±50 ppm									
6: ±25 ppm									
5: ±35 ppm									
Output Type									
F: Fixed									
T: Tristate									
Symmetry/Output Logic Type									
C: 45/55% CMOS									
L: 45/55% LVDS									
P: 45/55% PECL									
Package/Lead Configurations									
N: Leadless Ceramic									
Frequency (customer specified)									

Electrical Specifications	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
	Frequency Range	F	53.125		125	MHz	CMOS
			53.125		156.25	MHz	PECL/LVDS
	Operating Temperature	T _A	(See Ordering Information)				
	Storage Temperature	T _s	-55		+125	°C	
	Frequency Stability	ΔF/F	(See Ordering Information)				See Note 1
	Aging						
	1st Year			±2		ppm	
	Thereafter (per year)			±1		ppm	
	Input Voltage	V _{cc} /V _{dd}	3.135	3.3	3.465	V	
	Input Current	V _{dd} /I _{dd}			60	mA	CMOS/LVDS
					100	mA	PECL
	Output Type						CMOS/PECL/LVDS
	Load		15 pF				CMOS (See Note 2)
			50 Ohms to V _{cc} -2 VDC				PECL (See Note 3)
			100 Ohm differential load				LVDS (See Note 4)
	Symmetry (Duty Cycle)		45	50	55	%	50% V _{dd} (CMOS)
	(Per Symmetry Code)		45	50	55	%	V _{cc} -1.3 VDC (PECL)
			45	50	55	%	1.25 VDC (LVDS)
	Output Skew				200	ps	PECL
	Differential Voltage	V _o	250	340	450	mV	LVDS
	Logic "1" Level	V _{oh}	90% V _{dd}			V	CMOS
			V _{cc} -1.02			V	PECL
			1.375			V	LVDS
	Logic "0" Level	V _{ol}			10% V _{dd}	V	CMOS
					V _{cc} -1.63	V	PECL
					1.125	V	LVDS
	Output Current		-4		+4	mA	CMOS
	Rise/Fall Time	T _r /T _f		0.35	0.55	ns	CMOS @ 20/80%
				.50	1.0	ns	LVPECL @ 20/80%
							LVDS @ 20/80%
	Tristate Function		80% V _{dd} min or floating: output active				
			20% V _{dd} max: output disables to high-Z				
	Start up Time		5			ms	
	Peak to Peak Jitter (+/-)	T _J		10	15	ps	@ BER 1E-12 (See Note 5)
				15	20	ps	CMOS
							PECL/LVDS


1. Inclusive of initial tolerance, deviation over temperature, shock, vibration, voltage, and aging.
2. See load circuit diagram #2.
3. See load circuit diagram #5.
4. See load circuit diagram #9.
5. See jitter test circuit in Figure 1.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.


Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

M2001 Series


5x7 mm, 3.3 Volt, CMOS/LVPECL/LVDS, Clock Oscillator




CMOS Output



LVPECL/LVDS Output




SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Tristate/NC
2	Ground
3	Output
4	+Vdd


SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Tristate
2	N/C
3	Ground
4	Output1/ Q
5	Output2/ Q̅
6	+Vdd

Figure 1



MtronPTI Lead Free Solder Profile

