

TH-Q1201-A1 / TH-Q1301-A1 / TH-Q1401-A1

60W / 80W / 100W QUASI-CW LINEAR BAR ARRAYS

DESCRIPTION

The TH-Q1X01-A1 products are a high optical power laser diodes for quasi-CW operation. The 'X' in TH-Q1X06-A characterises the optical power of each bar For X = 2, 3, 4 respectively, peak optical power are 60W, 80W, 100W. These products are based on a quantum well design to realize highly efficient 1cm linear bar arrays. The quality of the process of these laser diodes leads to longer lifetime and improved reliability.

Assembly in a compact and rugged package allows easy connection to a heat exchanger to get good temperature control.

MAIN FEATURES

- 795nm to 860nm
- Liquid cooled package
- High conversion efficiency
- Very high temperature stability of operation
- Mechanically robust, shock and vibration resistant
- Highly reproducible MOCVD process



SPECIFICATIONS

Case temperature : 25 °C

Quasi-continuous mode : pulse width = 200µs
repetition rate = 100Hz

PARAMETERS	TH-Q1201-A1	TH-Q1301-A1	TH-Q1401-A1	UNITS
QCW output power	60	80	100	Watt
Energy per pulse	12	16	20	mJ
Emitting area	10 x 0.001	10 x 0.001	10 x 0.001	mm x mm
Threshold current typical max.	14 18	14 18	14 18	Amp.
Operating current (If) typical max.	65 70	86 94	102 113	Amp.
Operating voltage	<2	<2	<2	Volt
Total efficiency typical min.	49 43	49 43	49 43	%
$\Delta I_f / (I_f \Delta T)$ ¹	0.4	0.4	0.4	%/K
$\Delta \lambda / \Delta T$	0.26	0.26	0.26	nm/K
Beam divergence (FWHM)	10 x 40	10 x 40	10 x 40	degree
Spectral Width (FWHM)	< 3.5	< 3.5	< 4	nm

¹ Variation of operating current If with temperature

Note :

- Standard wavelength is 808nm +/-3nm
- Tolerance on wavelength is +/- 4nm (+/- 3nm upon request)
- **TH-Q1201-A1** can operate at higher duty cycles of over 20% (up to 1kHz) with optical output power up to 80W QCW

ABSOLUTE MAXIMUM RATINGS

PARAMETERS	TH-Q1201-A1	TH-Q1301-A1	TH-Q1401-A1	UNITS
QCW output power	65	85	105	Watt
Reverse voltage	3	3	3	Volt
Operating temperature	+5 to +50	+5 to +50	+5 to +50	°C
Storage temperature	-40 to +85	-40 to +85	-40 to +85	°C

Note : Operation at temperature below dew point requests to use dry N2 environment

For further information please contact:

THALES LASER DIODES - Route Départementale 128 - BP 46 - 91401 ORSAY Cedex / France

Tel : (33) 1 69 33 06 61

Fax : (33) 1 69 33 06 62

E-mail : infotld@fr.thalesgroup.com

<http://www.thales-laser-diodes.com>

Information furnished is believed to be accurate and reliable. However THALES LASER DIODES assumes no responsibility for the consequences of use of such information nor for any infringement or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of THALES LASER DIODES. Specifications mentioned in this publication are subjected to change without notice. This publication supersedes and replaces all informations previously supplied. THALES LASER DIODES products are not authorized for use as critical components in life support devices or systems without express written approval from THALES LASER DIODES. © 2001 THALES LASER DIODES Printed in France All rights reserved.