



NOTES.

1. REMOVE ALL BURRS AND SHARP EDGES.
2. COMPONENT TO BE FULLY ANNEALED BEFORE PLATING.

| PART No. | DIM 'A' | SURFACE AREA |
|----------|-----------|--------------|
| H9030-01 | 2.54/2.79 | 372.24 |
| H9031-01 | 3.30/3.56 | 383.38 |
| H9032-01 | 4.06/4.32 | 394.44 |

| | | |
|----|----------|------|
| 13 | 03.09.98 | 4543 |
| 12 | 25.11.93 | 2479 |
| 11 | 04.01.89 | 1384 |

ISS. DATE C/N

APPROVED:

CHECKED:

DRAWN: D. BECK

CUSTOMER REF.

ASSEMBLY DRG:

HARWIN

HARWIN INC
U.S.A.TEL: (812) 285 0055
FAX: (812) 285 0056HARWIN PLC
U.K.TEL: 01705 370451
FAX: 01705 314590HARWIN PTE
SINGAPORETEL: 65 7794909
FAX: 65 7793868

TOLERANCES

X. = ±1mm
 X.X = ±0.25mm
 X.XX = ±0.10mm
 X.XXX = ±0.01mm
 ANGLES = ±1°
 UNLESS STATED

MATERIAL:

BRASS CZ121 TO BS2874
(BRM1030)

FINISH: F0109 (TIN/LEAD)

S/AREA: SEE TABLE mm²

TITLE:

TERMINAL LUG

DRAWING NUMBER:

H9030/31/32-01

SHT
1 OF 1