



SPECIFICATIONS
 Current Rating: 7A AC/DC
 Insulation Resistance: 1000M Ω
 Contact Resistance: 20m Ω max
 Contact Material: Brass, Tin Plated
 Insulation Material: Nylon 66 UL94V-0
 Withstanding: 1500V AC
 Temperature Range: -25C to +105C

Dimensions		
Poles	A	B
2	3.96	8.25
3	7.92	12.21
4	11.88	16.17
5	15.84	20.13
6	19.80	24.09
7	23.76	28.05
8	27.72	32.01
9	31.68	35.97
10	35.64	39.93
11	39.60	43.89
12	43.56	47.85
13	47.52	51.81
14	51.48	55.77
15	55.44	59.73

Series	Type	Positions	Material	Color
JS-CH	1121	XX	X	XX
Pluggable Connector	Wire Mount Housing	02-15	Blank=Nylon 66 GF=Nylon 66 + Glass Fill	Blank=Natural (std) BK=Black BL=Blue

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	05/15/11
				Checked	Lizzy	05/15/11
				Drawn	Tina	05/15/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **JS-CH-1121-XX-XX-XX**

Description: 3.96mm Crimp Style Connector Housing

