



NEUTRIK

NA1394-6-B Firewire 6 Feedthrough

Due to the rising digitisation the interface problems between audio / video networks, IT equipment (e.g. Mac) and mLAN connections increase. Neutrik's Firewire feedthrough type 1394a, mounted in the standardized D-shape housing, solves this problem.

Firewire 6 with IEEE 1394 6-pol receptacles on both ends, Black D-housing.

Features & Benefits

- Ideal for audio networking and integration of digital equipment into audio systems
- Firewire feedthrough with 6 pole IEEE 1394 receptacle at both ends
- Universally accepted standard D-shape housing



Product

Connector type	Firewire
Gender	female

Electrical

Contact resistance	< 30 mΩ (mated pair)
Dielectric strength	0,5 kVdc (1 min)
Insulation resistance	> 1 GΩ
Rated current per contact	1,5 A
Rated Voltage	< 40 V dc

Mechanical

Insertion force	< 35 N
Withdrawal force	> 10 N
Lifetime	> 1,500 mating cycles
Chassis shape	D

Material

Contact Plating	Au
Contacts	CuZn36
Insert	Polyamide (PA 6)
Shell	Zinc diecast (ZnAl4Cu1)
Shell plating	Black chromium

Environmental

Flammability	UL 94 V-0
Temperature range	-25 °C to +85 °C



www.BroadcastInstallShop.com