



SD

SD

NOTES:

- FOR USE WITH RG-393/U CABLE.
- FOR CABLING INSTRUCTIONS SEE CP-5402.
- FOR CABLE TRIMMING USE KTJ-150 & KTD-138.
- FOR CRIMPING USE DIE KTH-2105.
- INTERFACE PER MIL-STD-348, FIG. 302-1.
- CENTER CONTACT F (1-534-84MA9) SUPPLIED UNASSEMBLED.
- MARK PACKAGE: KINGS 796-19-9 YRWK (DATE CODE) PATENT NO. 5277590
- CABLE END SWIVELS RELATIVE TO CUBE BODY.
- MATERIALS:
 - OUTER CONTACT-BER. COP., ASTM-B-196
 - K-GRIP SLEEVE-COMMERCIAL BRONZE, ASTM-B-140
 - GASKET-SILICONE RUBBER, ZZ-R-765
 - C-RING-PHOS. BRONZE, QQ-B-750
 - INSULATOR-TEFLON, ASTM-D-4894
 - ALL OTHER METAL PARTS-BRASS, ASTM-B16
- FINISHES:
 - OUTER CONTACT-SILVER PLATE PER QQ-S-365
 - CENTER CONTACTS-GOLD PLATE PER MIL-G-45204
 - ALL OTHER METAL PARTS-KINGS TARNISH RESISTANT NICKEL FINISH (TR-5)
- ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE-50 OHMS
 - FREQUENCY RANGE-DC TO 11 GHZ
 - WORKING VOLTAGE-1000 VRMS

796-19-9

REVISIONS	
ISSUE	CHANGES
0	ER 35841 KH 10/04/94
1	CN 37556 C MRM 01/29/98

796-199D

SCALE 4:1

APPROX SURFACE AREA

WAS: E-18325B

USED ON

REF: BOEING

PLUG, ANGEL, SWIVEL, C

DRAWN	KH	DATE	06/20/94
DESIGN	JT	DATE	06/21/94
APPR.		DATE	

KINGS
ELECTRONICS CO., INC.
TUCKAHOE, NEW YORK 10707

796-19-9