

**.300 Spade  
24-18 AWG**

**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS	
6	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-6-3		
						Pre Tinned Brass	A3A2-6-3		
8	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-8-3		
						Pre Tinned Brass	A3A2-8-3		
10	.075-.125	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-10-3		
						Pre Tinned Brass	A3A2-10-3		
6	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-5-3		
						Pre Tinned Brass	A3A2-5-3		
8	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-7-3		
						Pre Tinned Brass	A3A2-7-3		
10	None	✓ ✓	5000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	A3A1-9-3		
						Pre Tinned Brass	A3A2-9-3		

NOTE: UL & CSA do not recognize 24 AWG terminations.

**.300 Spade  
20-14 AWG**

**Spade and Ring Series  
Uninsulated**

STUD	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS	
4	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3A1-4		
						Pre Tinned Brass	3A2-4		
						.032	Brass		3A3-4
							Pre Tinned Brass		3A4-4
6	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3A1-6		
						Pre Tinned Brass	3A2-6		
						.032	Brass		3A3-6
							Pre Tinned Brass		3A4-6
8	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3A1-8		
						Pre Tinned Brass	3A2-8		
						.032	Brass		3A3-8
							Pre Tinned Brass		3A4-8
10	.075-.175	✓ ✓	4000	$\frac{5}{32} \pm \frac{1}{32}$	.020	Brass	3A1-10		
						Pre Tinned Brass	3A2-10		
						.032	Brass	3A3-10	
							Pre Tinned Brass	3A4-10	