



TE Internal #: 1-1932258-2

USB Connectors, A, 3.0, Standard Profile, Receptacle, 1 Port, Top, Right Angle, Box & Tray / Tray, Flush, Through Hole - Solder, Cable-to-Board

[View on TE.com >](#)

Connectors > Audio & Video Connectors > USB Connectors



USB Adapter Type: **A**

USB Version: **3.0**

Connector Profile: **Standard**

Connector & Housing Type: **Receptacle**

Number of Ports: **1**

Features

Product Type Features

USB Adapter Type	A
USB Version	3.0
Connector & Housing Type	Receptacle
Connector System	Cable-to-Board
Connector & Contact Terminates To	Printed Circuit Board
USB Connector Type	USB 3.0 Type-A

Configuration Features

Number of Mounting Legs	2
Number of Ports	1
Number of Positions	4

Body Features

Shell Plating Finish	Bright
Shell Plating Material	Tin
Connector Profile	Standard

Contact Features

Contact Mating Area Plating Material Thickness	.76 µm[29.92 µin]
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	1.8 A

Termination Features



Termination Post & Tail Length	2.3 mm[.091 in]
--------------------------------	-----------------

Termination Method to Printed Circuit Board	Through Hole - Solder
---	-----------------------

Mechanical Attachment

Locking Feature	Without
-----------------	---------

PCB Mount Location	Top
--------------------	-----

PCB Connector Seating	Flush
-----------------------	-------

PCB Mount Retention Type	Kinked Legs
--------------------------	-------------

Panel Mount Feature Type	Flange
--------------------------	--------

Connector Mounting Type	Board Mount
-------------------------	-------------

Housing Features

Housing Material	Thermoplastic
------------------	---------------

Housing Color	Blue
---------------	------

Body Orientation	Right Angle
------------------	-------------

Centerline (Pitch)	2 mm, 2.5 mm[.078 in][.098 in]
--------------------	--------------------------------

Dimensions

PCB Thickness (Recommended)	1.6 mm[.063 in]
-----------------------------	-----------------

Usage Conditions

Soldering Temperature (Max)	260 °C[500 °F]
-----------------------------	----------------

Mating Cycles (Max)	5000
---------------------	------

Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Halogen Free	Yes
--------------	-----

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Moisture Sensitivity Level	5a
----------------------------	----

Industry Standard	USB 3.0
-------------------	---------

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	144
--------------------	-----

Packaging Method	Box & Tray, Tray
------------------	------------------

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 1-2117155-0
C/A, USB3.0 A TYPE TO MICRO B,

Customers Also Bought



TE Part #5177983-4
0.8FH,R05H.5,100,08/Sn,TU



TE Part #2-1625984-2
Power Resistors: Aluminum Housed,
HSA



TE Part #3-5353652-6
.5FHP08H,440,B,GIG,08/Sn,HT,NSYes



TE Part #5177984-4
0.8FH,P05H.5,100,08/Sn,TU



TE Part #3-2198339-1
zSFP+ STACKED 2X6 RECEPTACLE
ASSEMBLY



TE Part #2-1825043-0
UP3DTBNLB04,MICROSWITCH,SNAP



TE Part #2320065-2
MINI IO CABLE ASSEMBLY



TE Part #2333781-7
MINI IO TO RJ45 CABLE ASSEMBLY,
L=4000MM

Documents

Product Drawings

Std USB 3,0, Type A, R/A, T/H

English

CAD Files

3D PDF

3D

Customer View Model

[ENG_CVM_CVM_1-1932258-2_C.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-1932258-2_C.3d_igs.zip](#)

English

Customer View Model

[ENG_CVM_CVM_1-1932258-2_C.3d_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

Product Specification

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English

