


SRD2.5-V

- 4 Connections

**PTR**

Phoenix Mecano Brand




Technical Data

Wire sizes		Insulating Material	
Solid min	0.2 mm ²	Material	PA 6.6
Solid max	4.0 mm ²	Flammability Class	UL 94 V-2
Stranded (flexible) min	0.2mm ²	Temperatures	
Stranded (flexible) max	4.0 mm ²	Working Temperature	-40 - 105 °C
Stranded with Ferrule min	0.2 mm ²	Dimensions	
Stranded with Ferrule max	2.5 mm ²	Stripped Length	7.0 mm
Clamping Range min	0.2mm ²	Width	5.0 mm
Clamping Range max	4.0 mm ²	Length	60.2 mm
		Height TS35 x 7.5	61.0 mm
		Height TS32	65.5 mm

Electrical Data**General**

Cross Connection Channels	1
Test Pick off	1

Colours

	BEIGE, similar RAL 1019
	BLUE, similar RAL 5015
	YELLOW, similar RAL 1023

Connection Diagram

Bitte kontaktieren Sie unsere Vertriebsmitarbeiter.
Please contact our sales department.

Order Data

Article Designation	Article Number	PU
SRD2.5-V-BEIGE	41209.2	100
SRD2.5-V-BLUE	41209.5	100

Accessoires

Article Designation	Article Number	PU
End Plate AP4	492101.2	20
Insulation Plates TRS3	492566.2	100
Cross-Connection uninsulated Q2	492567.0	50
Cross-Connection uninsulated Q3	492568.0	50
Cross-Connection uninsulated Q4	492569.0	20
Cross-Connection uninsulated Q10	492570.0	10
End Stopn ES35/K/ST	492828.0	50
Test Adapter TAD5/1/S	492821.0	10
Quick Labelling PSB5/50	494600.7	500

Ratings

Ratings	UR		IEC
	Rated Voltage	300 V	300 V
Rated Current	20 A	20 A	24 A
Rated Wire Size	AWG 22-14	AWG 22-14	2.5 mm ²
Rated Impulse Voltage			6 V
Pollution Degree			3