

Note: This datasheet may be out of date. Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLL18AG331A2E1H01%23

"#" indicates a package specification code.

## BLL18AG331A2E1H01#










< List of part numbers with package codes > BLL18AG331A2E1H01B



### Appearance & Shape









### **Applications**

Automotive Usage

Powertrain/Safety



### **Packaging Information**

Packaging		Standard
		Packing
		Quantity
В	Bulk(Bag)	500



### **Features**

1.BLL18Aseries is designed to function nearly as a resistor at noise frequencies, which greatly reduces the possibility of resonance and leaves signal wave forms undistorted.

BLL18Aseries is effective in circuits without stable ground lines because BLL18A series does not need a connection to ground.

- 2.BLL18Aseries is effective in noise suppression in a wide frequency range (30MHz to several hundred MHz).
- 3.Lead-free Halogen-free is available.
- 4. Flow soldering. Corresponds to the welding implementation. (Not supported Reflow soldering.)
- 5. The material can be changed to a Cu wire according to the welding material as required.

1 of 3

- 1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.
- 2. This datasheet has only typical specifications because there is no space for detailed specifications
- Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





# BLL18AG331A2E1H01#

Note: This datasheet may be out of date.

Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en/products/productdetail?partno=BLL18AG331A2E1H01%23

"#" indicates a package specification code.



# **Specifications**

Shape	Lead
Length	4.5mm
Length Tolerance	max.
Width	3.0mm
Width Tolerance	max.
Thickness	4.0mm
Thickness Tolerance	max.
Operating Temperature Range	-40°C to 150°C
Mass(typ.)	0.13g
Number of Circuit	1
Rated Current (at 85°C)	200mA
Rated Current (at 125°C)	200mA
Rated Current (at 150°C)	200mA
DC Resistance(max.)	0.6Ω
Impedance (at 100MHz)	330Ω
Impedance (at 100MHz) Tolerance	±40%

2 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.



#### Product Search Data Sheet

Note: This datasheet may be out of date.


Please download the latest datasheet of BLL18AG331A2E1H01# from the official website of Murata Manufacturing Co., Ltd.


http://www.murata.com/en/products/productdetail?partno=BLL18AG331A2E1H01%23

"#" indicates a package specification code.

# BLL18AG331A2E1H01#







Impedance-Frequency Characteristics

**Equivalent Circuit** 

3 of 3

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

