






PIN RECEPTACLES

FOR 0,51 - 0,81 DIAMETER PINS

| | | | |
|---|---|--|--|
| <p>0338 0338-0-15-XX-15-XX-10-0 Solder mount in 1,45 min. mounting hole Also available on 12mm wide carrier tape: 1,700 parts per 330mm reel Order as: 0338-0-57-XX-15-XX-10-0</p>  | <p>0378 0378-0-15-XX-15-XX-10-0 Solder mount in 2,08 min. mounting hole</p>  | <p>6002 6002-0-19-XX-15-XX-10-0 Solder mount in 1,5 min. mounting hole Wire Termination. Accepts wire sizes 26 AWG Max. / 30 AWG Min.</p>  | <p>7009 7009-0-19-XX-15-XX-10-0 Press-fit in 1,6 min. mounting hole Wire Termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.</p>  |
| <p>0339 0339-0-15-XX-15-XX-10-0 Solder mount in 1,45 min. mounting hole</p>  | | | |
| | | | |

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard
Contact Material: Beryllium Copper Alloy 172, HT
Dimensions: Millimeters
Tolerances On: Lengths: ± 0,13
 Diameters: ± 0,051
 Angles: ± 2°



ORDER CODE: XXXX - X - 1X - XX - 15 - XX - 10 - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 15 0,25µm GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 5,08µm TIN/LEAD OVER NICKEL
- ◆ 80 5,08µm TIN OVER NICKEL (RoHS)
- ◆ 27 0,76µm GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#15 CONTACT (DATA ON PAGE 254)

(For alternate contact choices, see group K on page 248)

