

**— Cross Bridge Design —
To Accept .187 x .020 Male Tab**

**.187 Quick-Connect Series
Flag Type**

WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
20-16	None	✓ ✓	3000	$\frac{5}{32} \pm \frac{1}{32}$.016	Pre Tinned Brass	3500H 414A*	
						Brass	3500H 414AB*	
* Recommended for application with CS-21 Auto Connect System								

20-16	.100-.150	— —	3000	$\frac{1}{4} \pm \frac{1}{32}$.016	Pre Tinned Brass	3500H 405A	
						Brass	3500H 405AB	

**— Axial Bridge Design —
To Accept .187 x .020 Male Tab**

**.187 Quick-Connect Series
Flag Type**

WIRE RANGE	INSULATION RANGE	UL / CSA	QUANTITY PER REEL	RECOMMENDED STRIP LENGTH	STOCK THICKNESS	MATERIAL AND FINISH	PART NUMBER	STYLE AND DIMENSIONS
22-16	None	✓ ✓	8000	$\frac{9}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3500H 4A	
						Brass	3500H 4AB	

22-16	None	✓ ✓	5000	$\frac{9}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3500H 404A*	
						Brass	3500H 404AB*	
* Recommended for Application with CS-21 Auto Connect System								

20-16	.075-.125	✓ ✓	8000	$\frac{5}{32} \pm \frac{1}{32}$.020	Pre Tinned Brass	3500H 11A	
						Brass	3500H 11AB	

S
T
C
E
N
O
C
K
I
P