



All dimensions are in mm; tolerances acc. ISO 2768 m-H

**Interface**

According to CECC 22 220, IEC 60169-36

**Documents**

Assembly instruction 29 C

**Material and plating**

**Connector parts**

Center contact  
Outer contact  
Dielectric  
Crimping sleeve

**Material**

Brass  
Beryllium copper  
PTFE  
Copper

**Plating**

Gold, min. 1.27 µm, over chemical nickel  
Gold, min. 0.8 µm, over chemical nickel  
Gold, 0.1 µm min.

**Electrical data**

Impedance	50 Ω
Frequency	DC to 6 GHz
Return loss	≥ 32 dB, DC to 2 GHz ≥ 26 dB, 2 to 4 GHz
Insertion loss	≤ 0.05 x √f(GHz) dB, DC to 4 GHz
Insulation resistance	≥ 1 GΩ
Center contact resistance	≤ 5.0 mΩ
Outer contact resistance	≤ 2.5 mΩ
Test voltage	750 V rms
Working voltage	335 V rms
Contact Current	1.5A DC max.

- Limitations are possible due to the used cable type -

**Mechanical data**

Mating cycles	≥ 500
Center contact captivation	≥ 10 N
Engagement force	≤ 25 N
Disengagement force	8 N min. to 20 N max.

**Environmental data**

Temperature range	-55°C to +155°C
Thermal shock	CECC 22 220, Chapter 4.6.7
Vibration	CECC 22 220, Chapter 4.6.3
Corrosion	CECC 22 220, Chapter 4.6.10
Moisture resistance	CECC 22 220, Chapter 4.6.6

**Tooling**

Crimping tool	11W150-000
Crimp insert	11W150-102

**Suitable cables**

RG 316 /U, RG 174 A/U, RG 188 A/U

**Packing**

Standard	100 pcs in bag
Weight	1.0 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Inge Mühlauer	07/09/04	Chr. Entfellner	23/02/05	a00	04-0130	Rong Fang	23/02/05
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany <a href="http://www.rosenberger.de">www.rosenberger.de</a>					Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: <a href="mailto:info@rosenberger.de">info@rosenberger.de</a>		Page 2 / 2