
HM62V16102I Series

Wide Temperature Range Version
16 M SRAM (1-Mword $\times$ 16-bit)

HITACHI

ADE-203-1248A(Z)
Preliminary
Rev. 0.1
Sep. 27, 2001

Description

The Hitachi HM62V16102I Series is 16-Mbit static RAM organized 1-Mword $\times$ 16-bit. HM62V16102I Series has realized higher density, higher performance and low power consumption by employing Hi-CMOS process technology. It offers low power standby power dissipation; therefore, it is suitable for battery backup systems. It is packaged in 48 bumps chip size package with 0.75 mm bump pitch for high density surface mounting.

Features

- Single 2.5 V and 3.0 V supply: 2.2 V to 3.6 V
- Fast access time: 25/35 ns (max)
- Page access time: 15/20 ns (max)
- Power dissipation:
 - Active: TBD (typ)
 - Standby: 1.5 μ W (typ)
- Completely static memory.
 - No clock or timing strobe required
- Equal access and cycle times
- Common data input and output.
 - Three state output
- Battery backup operation.
 - 2 chip selection for battery backup
- Temperature range: -40 to $+85^{\circ}\text{C}$

Preliminary: The specification of this device are subject to change without notice. Please contact your nearest Hitachi's Sales Dept. regarding specification.


HM62V16102I Series

Ordering Information

Type No.	Access time	Package
HM62V16102LBPI-2	25 ns	48-bumps CSP with 0.75 mm bump pitch (TBD)
HM62V16102LBPI-3	35 ns	
HM62V16102LBPI-2SL	25 ns	
HM62V16102LBPI-3SL	35 ns	

Pin Arrangement

48-bumps CSP



(Top view)

Pin Description

Pin name	Function
A0 to A19	Address input
I/O0 to I/O15	Data input/output
CS1	Chip select 1
CS2	Chip select 2
WE	Write enable
OE	Output enable
LB	Lower byte select
UB	Upper byte select
V _{cc}	Power supply
V _{ss}	Ground
NU* ¹	Not used (test mode pin)

Note: 1. This pin should be connected to a ground (V_{ss}), or not be connected (open).

Block Diagram

TBD

Operation Table

$\overline{\text{CS1}}$	CS2	$\overline{\text{WE}}$	$\overline{\text{OE}}$	$\overline{\text{UB}}$	$\overline{\text{LB}}$	I/O0 to I/O7	I/O8 to I/O15	Operation
H	x	x	x	x	x	High-Z	High-Z	Standby
x	L	x	x	x	x	High-Z	High-Z	Standby
x	x	x	x	H	H	High-Z	High-Z	Standby
L	H	H	L	L	L	Dout	Dout	Read
L	H	H	L	H	L	Dout	High-Z	Lower byte read
L	H	H	L	L	H	High-Z	Dout	Upper byte read
L	H	L	x	L	L	Din	Din	Write
L	H	L	x	H	L	Din	High-Z	Lower byte write
L	H	L	x	L	H	High-Z	Din	Upper byte write
L	H	H	H	x	x	High-Z	High-Z	Output disable

Note: H: V_{IH} , L: V_{IL} , x: V_{IH} or V_{IL}

Absolute Maximum Ratings

Parameter	Symbol	Value	Unit
Power supply voltage relative to V_{SS}	V_{CC}	-0.5 to + 4.6	V
Terminal voltage on any pin relative to V_{SS}	V_{T}	-0.5* ¹ to V_{CC} + 0.3* ²	V
Power dissipation	P_{T}	1.0	W
Storage temperature range	Tstg	-55 to +125	°C
Storage temperature range under bias	Tbias	-40 to +85	°C

Notes: 1. V_{T} min: -2.0 V for pulse half-width ≤ 10 ns.

2. Maximum voltage is +4.6 V.

DC Operating Conditions

Parameter	Symbol	Min	Typ	Max	Unit	Note
Supply voltage	V_{CC}	2.2	2.5/3.0	3.6	V	
	V_{SS}	0	0	0	V	
Input high voltage	V_{IH}	$0.75 \times V_{\text{CC}}$	—	$V_{\text{CC}} + 0.3$	V	
Input low voltage	V_{IL}	-0.3	—	$0.25 \times V_{\text{CC}}$	V	1
Ambient temperature range	Ta	-40	—	85	°C	

Note: 1. V_{IL} min: -2.0 V for pulse half-width ≤ 10 ns.

DC Characteristics

Parameter	Symbol	Min	Typ* ¹	Max	Unit	Test conditions
Input leakage current	$ I_{LI} $	—	—	1	μA	$V_{in} = V_{SS} \text{ to } V_{CC}$
Output leakage current	$ I_{LO} $	—	—	1	μA	$\overline{CS1} = V_{IH} \text{ or } CS2 = V_{IL} \text{ or}$ $\overline{OE} = V_{IH} \text{ or } \overline{WE} = V_{IL} \text{ or}$ $\overline{LB} = \overline{UB} = V_{IH}, V_{I/O} = V_{SS} \text{ to } V_{CC}$
Operating current	I_{CC}	—	—	1	mA	$\overline{CS1} = 0.2 \text{ V}, CS2 = V_{CC} - 0.2 \text{ V},$ Others = $V_{CC} - 0.2 \text{ V}/0.2 \text{ V},$ $I_{I/O} = 0 \text{ mA}$
Average operating current	I_{CC1}	—	—	50	mA	Min. cycle, duty = 100%, $I_{I/O} = 0 \text{ mA}, \overline{CS1} = V_{IL}, CS2 = V_{IH},$ Others = V_{IH}/V_{IL}
	I_{CC2}	—	—	15	mA	Cycle time = 70 ns, duty = 100%, $I_{I/O} = 0 \text{ mA}, \overline{CS1} = 0.2 \text{ V},$ $CS2 = V_{CC} - 0.2 \text{ V},$ Others = $V_{CC} - 0.2 \text{ V}/0.2 \text{ V}$
	I_{CC3}	—	—	5	mA	Cycle time = 1 μs , duty = 100%, $I_{I/O} = 0 \text{ mA}, \overline{CS1} \leq 0.2 \text{ V},$ $CS2 \geq V_{CC} - 0.2 \text{ V}$ $V_{IH} \geq V_{CC} - 0.2 \text{ V}, V_{IL} \leq 0.2 \text{ V}$
Standby current	I_{SB1}^{*2}	—	0.5	30	μA	$0 \text{ V} \leq V_{in}$ (1) $0 \text{ V} \leq CS2 \leq 0.2 \text{ V}$ or (2) $\overline{CS1} \geq V_{CC} - 0.2 \text{ V},$ $CS2 \geq V_{CC} - 0.2 \text{ V}$ or (3) $\overline{LB} = \overline{UB} \geq V_{CC} - 0.2 \text{ V},$ $CS2 \geq V_{CC} - 0.2 \text{ V},$ $\overline{CS1} \leq 0.2 \text{ V}$
	I_{SB1}^{*3}	—	0.5	5	μA	
Output high voltage	$V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$ V_{OH}	2.2	—	—	V	$I_{OH} = -1 \text{ mA}$
	$V_{CC} = 2.2 \text{ V to } 3.6 \text{ V}$ V_{OH}	$V_{CC} - 0.2$	—	—	V	$I_{OH} = -100 \mu\text{A}$
Output low voltage	$V_{CC} = 2.7 \text{ V to } 3.6 \text{ V}$ V_{OL}	—	—	0.4	V	$I_{OL} = 2 \text{ mA}$
	$V_{CC} = 2.2 \text{ V to } 3.6 \text{ V}$ V_{OL}	—	—	0.2	V	$I_{OL} = 100 \mu\text{A}$

Notes: 1. Typical values are at $V_{CC} = 2.5 \text{ V}/3.0 \text{ V}$, $T_a = +25^\circ\text{C}$ and not guaranteed.

2. This characteristic is guaranteed only for L-version.

3. This characteristic is guaranteed only for L-SL version.

Capacitance ($T_a = +25^\circ\text{C}$, $f = 1.0\text{ MHz}$)


Parameter	Symbol	Min	Typ	Max	Unit	Test conditions	Note
Input capacitance	C_{in}	—	—	8	pF	$V_{in} = 0\text{ V}$	1
Input/output capacitance	$C_{i/o}$	—	—	10	pF	$V_{i/o} = 0\text{ V}$	1

Note: 1. This parameter is sampled and not 100% tested.

AC Characteristics ($T_a = -40$ to $+85^\circ\text{C}$, $V_{CC} = 2.2$ V to 3.6 V, unless otherwise noted.)

Test Conditions

- Input pulse levels: $V_{IL} = 0$ V, $V_{IH} = V_{CC}$
- Input rise and fall time: 3 ns
- Input and output timing reference levels: $0.5 \times V_{CC}$
- Output load: See figures (Including scope and jig)



Read Cycle

Parameter	Symbol	HM62V16102I				Unit	Notes
		-2		-3			
		Min	Max	Min	Max		
Read cycle time	t _{RC}	25	—	35	—	ns	
Address access time	t _{AA}	—	25	—	35	ns	
Chip select access time	t _{ACS1}	—	25	—	35	ns	
	t _{ACS2}	—	25	—	35	ns	
Output enable to output valid	t _{OE}	—	15	—	20	ns	
Output hold from address change	t _{OH}	5	—	5	—	ns	
$\overline{LB}$, $\overline{UB}$ access time	t _{BA}	—	25	—	35	ns	
Chip select to output in low-Z	t _{CLZ1}	5	—	5	—	ns	2, 3
	t _{CLZ2}	5	—	5	—	ns	2, 3
$\overline{LB}$, $\overline{UB}$ enable to low-z	t _{BLZ}	5	—	5	—	ns	2, 3
Output enable to output in low-Z	t _{OLZ}	3	—	3	—	ns	2, 3
Chip deselect to output in high-Z	t _{CHZ1}	0	12	0	15	ns	1, 2, 3
	t _{CHZ2}	0	12	0	15	ns	1, 2, 3
$\overline{LB}$, $\overline{UB}$ disable to high-Z	t _{BHZ}	0	12	0	15	ns	1, 2, 3
Output disable to output in high-Z	t _{OHZ}	0	12	0	15	ns	1, 2, 3

Page Mode Cycle

		HM62V16102I					
		-2		-3			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
Page read cycle time	t _{PC}	15	—	20	—	ns	
Page address access time	t _{PA}	—	15	—	20	ns	


Write Cycle

		HM62V16102I					
		-2		-3			
Parameter	Symbol	Min	Max	Min	Max	Unit	Notes
Write cycle time	t _{WC}	25	—	35	—	ns	
Address valid to end of write	t _{AW}	20	—	30	—	ns	
Chip selection to end of write	t _{CW}	20	—	30	—	ns	5
Write pulse width	t _{WP}	20	—	25	—	ns	4
$\overline{LB}$, $\overline{UB}$ valid to end of write	t _{BW}	20	—	30	—	ns	
Address setup time	t _{AS}	0	—	0	—	ns	6
Write recovery time	t _{WR}	0	—	0	—	ns	7
Data to write time overlap	t _{DW}	15	—	15	—	ns	
Data hold from write time	t _{DH}	0	—	0	—	ns	
Output active from end of write	t _{OW}	5	—	5	—	ns	2
Output disable to output in High-Z	t _{OHZ}	0	12	0	15	ns	1, 2
Write to output in high-Z	t _{WHZ}	0	12	0	15	ns	1, 2


- Notes: 1. t_{CHZ} , t_{OHZ} , t_{WHZ} and t_{BHZ} are defined as the time at which the outputs achieve the open circuit conditions and are not referred to output voltage levels.
2. This parameter is sampled and not 100% tested.
3. At any given temperature and voltage condition, t_{HZ} max is less than t_{LZ} min both for a given device and from device to device.
4. A write occurs during the overlap of a low $\overline{CS1}$, a high CS2, a low $\overline{WE}$ and a low $\overline{LB}$ or a low $\overline{UB}$. A write begins at the latest transition among $\overline{CS1}$ going low, CS2 going high, $\overline{WE}$ going low and $\overline{LB}$ going low or $\overline{UB}$ going low. A write ends at the earliest transition among $\overline{CS1}$ going high, CS2 going low, $\overline{WE}$ going high and $\overline{LB}$ going high or $\overline{UB}$ going high. t_{WP} is measured from the beginning of write to the end of write.
5. t_{CW} is measured from the later of $\overline{CS1}$ going low or CS2 going high to the end of write.
6. t_{AS} is measured from the address valid to the beginning of write.
7. t_{WR} is measured from the earliest of $\overline{CS1}$ or $\overline{WE}$ going high or CS2 going low to the end of write cycle.

Timing Waveform


Read Cycle




Page Mode Cycle




Write Cycle (1) ($\overline{\text{WE}}$ Clock)



Write Cycle (2) ($\overline{\text{CS}}$ Clock, $\overline{\text{OE}} = V_{\text{IH}}$)



Write Cycle (3) ($\overline{\text{LB}}$, $\overline{\text{UB}}$ Clock, $\overline{\text{OE}} = V_{\text{IH}}$)




Low V_{CC} Data Retention Characteristics ($T_a = -40$ to $+85^\circ\text{C}$)


Parameter	Symbol	Min	Typ ^{*4}	Max	Unit	Test conditions ^{*3}
V_{CC} for data retention	V_{DR}	1.2	—	3.6	V	$V_{in} \geq 0V$ (1) $0V \leq CS2 \leq 0.2V$ or (2) $CS2 \geq V_{CC} - 0.2V$, $\overline{CS1} \geq V_{CC} - 0.2V$ or (3) $\overline{LB} = \overline{UB} \geq V_{CC} - 0.2V$, $CS2 \geq V_{CC} - 0.2V$, $\overline{CS1} \leq 0.2V$
Data retention current	I_{CCDR}^{*1}	—	0.5	30	μA	$V_{CC} = 1.5V$, $V_{in} \geq 0V$ (1) $0V \leq CS2 \leq 0.2V$ or (2) $CS2 \geq V_{CC} - 0.2V$, $\overline{CS1} \geq V_{CC} - 0.2V$ or (3) $\overline{LB} = \overline{UB} \geq V_{CC} - 0.2V$, $CS2 \geq V_{CC} - 0.2V$, $\overline{CS1} \leq 0.2V$
	I_{CCDR}^{*2}	—	0.5	5	μA	
Chip deselect to data retention time	t_{CDR}	0	—	—	ns	See retention waveform
Operation recovery time	t_R	t_{RC}^{*5}	—	—	ns	

- Notes: 1. This characteristic is guaranteed only for L-version.
 2. This characteristic is guaranteed only for L-SL version.
 3. CS2 controls address buffer, $\overline{WE}$ buffer, $\overline{CS1}$ buffer, $\overline{OE}$ buffer, $\overline{LB}$, $\overline{UB}$ buffer and Din buffer. If CS2 controls data retention mode, V_{in} levels (address, $\overline{WE}$, $\overline{OE}$, $\overline{CS1}$, $\overline{LB}$, $\overline{UB}$, I/O) can be in the high impedance state. If $\overline{CS1}$ controls data retention mode, CS2 must be $CS2 \geq V_{CC} - 0.2V$ or $0V \leq CS2 \leq 0.2V$. The other input levels (address, $\overline{WE}$, $\overline{OE}$, $\overline{LB}$, $\overline{UB}$, I/O) can be in the high impedance state.
 4. Typical values are at $V_{CC} = 1.5V$, $T_a = +25^\circ\text{C}$ and not guaranteed.
 5. t_{RC} = read cycle time.


Low V_{CC} Data Retention Timing Waveform (1) ($\overline{CS1}$ Controlled)



Low V_{CC} Data Retention Timing Waveform (2) ($CS2$ Controlled)



Low V_{CC} Data Retention Timing Waveform (3) ($\overline{LB}$, $\overline{UB}$ Controlled)



HM62V16102I Series

Package Dimensions

HM62V16102LBPI Series (TBD)

TBD

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: (03) 3270-2111 Fax: (03) 3270-5109

URL <http://www.hitachisemiconductor.com/>

For further information write to:

Hitachi Semiconductor (America) Inc.
179 East Tasman Drive
San Jose, CA 95134
Tel: <1> (408) 433-1990
Fax: <1> (408) 433-0223

Hitachi Europe Ltd.
Electronic Components Group
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 585200

Hitachi Europe GmbH
Electronic Components Group
Dornacher StraÙe 3
D-85622 Feldkirchen
Postfach 201, D-85619 Feldkirchen
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Asia Ltd.
Hitachi Tower
16 Collyer Quay #20-00
Singapore 049318
Tel: <65>-538-6533/538-8577
Fax: <65>-538-6933/538-3877
URL: <http://semiconductor.hitachi.com.sg>

Hitachi Asia Ltd.
(Taipei Branch Office)
4/F, No. 167, Tun Hwa North Road
Hung-Kuo Building
Taipei (105), Taiwan
Tel: <886>-(2)-2718-3666
Fax: <886>-(2)-2718-8180
Telex: 23222 HAS-TP
URL: <http://www.hitachi.com.tw>

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7/F., North Tower
World Finance Centre,
Harbour City, Canton Road
Tsim Sha Tsui, Kowloon Hong Kong
Tel: <852>-(2)-735-9218
Fax: <852>-(2)-730-0281
URL: <http://semiconductor.hitachi.com.hk>

Copyright © Hitachi, Ltd., 2001. All rights reserved. Printed in Japan.

Colophon 5.0