

SEMELAB

T-33-01

Type No.	Reliability Option	Polarity	Package	V _{CEO}	I _C cont	h _{FE} @	V _{CE} /I _C	f _T	P _D
BDW51A	HI-REL	NPN	TO3	60	15	20-150	4/5		
BDW51B	HI-REL	NPN	* TO3	80	15	20-150	4/5	2.5M	117
BDW51C	HI-REL	NPN	* TO3	100	15	20-150	4/5	2.5M	117
BDW52	HI-REL	PNP	* TO3	45	15	20-150	4/5	2.5M	117
BDW52A	HI-REL	PNP	* TO3	60	15	20-150	4/5	2.5M	117
BDW52B	HI-REL	PNP	* TO3	80	15	20-150	4/5	2.5M	117
BDW52C	HI-REL	PNP	* TO3	100	15	20-150	4/5	2.5M	117
BDW53		NPN	TO220	45	4	750-20k	3/1.5	1M	40
BDW53A		NPN	TO220	60	4	750-20k	3/1.5	1M	40
BDW53B		NPN	TO220	80	4	750-20k	3/1.5	1M	40
BDW53C		NPN	TO220	100	4	750-20k	3/1.5	1M	40
BDW54		PNP	TO220	45	4	750-20k	3/1.5	1M	40
BDW54A		PNP	TO220	60	4	750-20k	3/1.5	1M	40
BDW54B		PNP	TO220	80	4	750-20k	3/1.5	1M	40
BDW54C		PNP	TO220	100	4	750-20k	3/1.5	1M	40
BDW63		NPN	TO220	45	6	750-20k	3/2	1M	60
BDW64		PNP	TO220	45	6	750-20k	3/2	1M	60
BDW73		NPN	TO220	45	8	750-20k	3/3	1M	80
BDW73A		NPN	TO220	60	8	750-20k	3/3	1M	80
BDW73B		NPN	TO220	80	8	750-20k	3/3	1M	80
BDW73C		NPN	TO220	100	8	750-20k	3/3	1M	80
BDW74		PNP	TO220	45	8	750-20k	3/3	1M	80
BDW74A		PNP	TO220	60	8	750-20k	3/3	1M	80
BDW74B		PNP	TO220	80	8	750-20k	3/3	1M	80
BDW74C		PNP	TO220	100	8	750-20k	3/3	1M	80
BDW83		NPN	TO3	45	15	750-20k	3/6	1M	150
BDW83A		NPN	TO3	60	15	750-20k	3/6	1M	150
BDW83B		NPN	TO3	80	15	750-20k	3/6	1M	150
BDW83C		NPN	TO3	100	15	750-20k	3/6	1M	150
BDW84		PNP	TO3	45	15	750-20k	3/6	1M	150
BDW84A		PNP	TO3	60	15	750-20k	3/6	1M	150
BDW84B		PNP	TO3	80	15	750-20k	3/6	1M	150
BDW84C		PNP	TO3	100	15	750-20k	3/6	1M	150
BDW93		NPN	TO220	45	12	750-20k	3/5	20M	80
BDW93A		NPN	TO220	60	12	750-20k	3/5	20M	80
BDW94B		NPN	TO220	80	12	750-20k	3/5	20M	80
BDW93C		NPN	TO220	100	12	750-20k	3/5	20M	80
BDW94		PNP	TO220	45	12	750-20k	3/5	20M	80
BDW94A		PNP	TO220	60	12	750-20k	3/5	20M	80
BDW94B		PNP	TO220	80	12	750-20k	3/5	20M	80
BDW94C		PNP	TO220	100	12	750-20k	3/5	20M	80
BDX10	HI-REL	NPN	* TO3	60	15	20-70	4/4		
BDX11	HI-REL	NPN	* TO3	140	10	20-70	4/3		
BDX12		NPN	* TO3	120	5	20-70	4/2		
BDX13	HI-REL	NPN	* TO3	40	15	15-60	4/8		

* Die available to meet this electrical specification