


P2 CONN TYPE	FIG NO	P1 CONN TYPE							
		BJ20		UBJ20		BJ40		UBJ40	
		SCHEMATICS							
		K1	K2	K1	K2	K1	K2	K1	K2
		DASH NUMBERS							
CJ20	1A	△	-1	-2	-3	△	-5	-6	-7
UCJ20		-8	-9	△	-10	-11	-12	△	-14
CJ40	1B	△	-15	-16	-17	△	-18	-19	-20
UCJ40		-21	-22	△	-23	-24	-25	△	-26
BJ26	2A	△	-27	-28	-29	△	-30	-31	-32
UBJ26		-33	-34	△	-35	-36	-37	△	-38
BJ46	2B	△	-39	-40	-41	△	-42	-43	-44
UBJ46		-45	-46	△	-47	-48	-49	△	-50
BJ29	3A	△	-51	-52	-53	-54	-55	-56	-57
UBJ29		-59	-60	-61	-62	-63	-64	-65	-66
BJ49	3B	△	-67	-68	-69	-70	-71	-72	-73
UBJ49		-75	-76	-77	-78	-79	-80	-81	-82
PL20	4A	△	-83	-84	-85	-86	-87	-88	-89
UPL20		-91	-92	-93	-94	-95	-96	-97	-98
PL40	4B	△	-99	-100	-101	-102	-103	-104	-105
UPL40		-107	-108	-109	-110	-111	-112	-113	-114
PL122	5A	△	-115	-116	-117	△	-118	-119	-120
UPL122		-121	-122	△	-123	-124	-125	△	-126
PL123	5B	△	-127	-128	-129	-130	-131	-132	-133
UPL123		-135	-136	-137	-138	-139	-140	-141	-142



INCH	MM
.005	0.13
.030	0.76
.143	3.63
.156	3.96
.218	5.54
.221	5.61
.281	7.14
.284	7.21
.436	11.07
.440	11.16
.475	12.05
.480	12.19
.500	12.70
.505	12.83
.510	12.83
.570	14.48
.594	15.09
.630	16.00
.635	16.13
.687	17.45
.810	20.57
1.427	36.25
1.452	36.88
1.518	38.56
1.521	38.63

RED INDICATES ORIGINAL

- △ FOR "K1" VERSION SEE 1-0440-2,UAD142
- △ FOR "K1" VERSION SEE 1-0440-1,AD142
- △ FOR "K1" VERSION SEE 1-0423-2,UAD122
- △ FOR "K1" VERSION SEE 1-0423-1,AD122
- △ FOR "K1" VERSION SEE 1-0048-2,UBJ48
- △ FOR "K1" VERSION SEE 1-0048-1,BJ48
- △ FOR "K1" VERSION SEE 105-1049-2,UBJ2848
- △ FOR "K1" VERSION SEE 105-1049-1,BJ2848
- △ FOR "K1" VERSION SEE 105-1049-4,UBJ4828
- △ FOR "K1" VERSION SEE 105-1049-3,BJ4828
- △ FOR "K1" VERSION SEE 1-0133-2,UBJ28
- △ FOR "K1" VERSION SEE 1-0133-1,BJ28
- △ FOR "K1" VERSION SEE 1-0470-2,UAD48
- △ FOR "K1" VERSION SEE 1-0470-1,AD48
- △ FOR "K1" VERSION SEE 105-1044-2,UAD2848
- △ FOR "K1" VERSION SEE 105-1044-1,AD2848
- △ FOR "K1" VERSION SEE 1-0469-2,UAD28
- △ FOR "K1" VERSION SEE 1-0469-1,AD28
- 3 50 & 75 OHM COAXIAL BNC/TNC JACK TO 50 & 75 OHM COAXIAL BNC/TNC JACK/INSULATED AND NONINSULATED BULKHEAD MOUNT JACK/PLUG/ NONINSULATED BULKHEAD MOUNT PLUG/PUSH-ON PLUG
- 2 TFS-1A (NICKEL)
- 1 ALL DIM ARE IN INCHES

23. EXAMPLE OF COMPLETE MODEL NO:

AD-BJ20-K1-CJ20

ADAPTER P1 CONN SCHEMATIC P2 CONN

22. EXAMPLE OF COMPLETE PART NO:

12-03-1

BASIC PART NO DASH NO

DATA CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO TROMPETER ELECTRONICS INC. AND SHALL NOT BE DISCLOSED, COPIED OR USED FOR PROCUREMENT OR MANUFACTURE WITHOUT EXPRESS WRITTEN PERMISSION OF TROMPETER ELECTRONICS INC.

REVISIONS		12-03	SH 1
REV	DESCRIPTION	DATE	APPROVED
C	REVISED PER ECD 14198	7-5-01	

FIG 1A (P1)

-2 SHOWN

-24 SHOWN

FIG 1B (P2)








FIG 2A (P1)

-27 SHOWN

-42 SHOWN

FIG 2B (P1)






RECOMMENDED
PANEL CUTOUT
FOR -27 THRU -50
MAX PNL THK .143

FIG 3A (P1)

-51 SHOWN

-71 SHOWN

FIG 3B (P1)



RECOMMENDED
PANEL CUTOUT
FOR -51 THRU -82
MAX PNL THK .218

FIG 4A (P1)

-83 SHOWN

-103 SHOWN

FIG 4B (P1)








FIG 5A (P1)

-115 SHOWN

-131 SHOWN

FIG 5B (P1)



RECOMMENDED
PANEL CUTOUT
FOR -115 THRU -126
MAX PNL THK .156

INTERPRET DRAWING PER MIL-STD-100 DIMENSIONS ARE IN INCHES AND INCLUDE FINISH THICKNESS UNLESS OTHERWISE SPECIFIED		TOL: UNLESS SPECIFIED .XX ± .02 .XXX ± .010 .XXXX ANGLES		
DRAWN JCM	DATE 8-23-01	MATERIAL: △		
CHECKED M.A.	8/2/01	FINISH:	TITLE: ADAPTERS: FEMALE BNC/TNC SERIES TO MALE/FEMALE BNC/TNC & MALE/FEMALE BULKHEAD MOUNT BNC/TNC SERIES	
QUALITY			SIZE B	CAGE CODE 14949
MANUF			DRAWING NO. 12-03	REV C
APPROVED			SCALE 2/1	DATE: 4-23-86
NEXT ASSY	CAD FILE NO 12-03C1	DO NOT SCALE DWG	SHEET 1 OF 2	