



NOTES: FINISH (PLATING THICKNESS IN MICRO-INCHES)

- 1. BRASS PER QQ-B-626
- 2. BRASS PER QQ-B-613
- 3. NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 4. PHOSPHOR BRONZE PER QQ-B-750
- 5. GOLD PL. 30 MIN. THICK OVER NICKEL PL. 100 MIN. THICK OVER COPPER STRIKE
- 6. TEFLON MIL-P-19468

1. MAX. PANEL THICKNESS=3.2mm

DIMENSIONS ARE IN MILLIMETERS										PART NO. MU6451B1-NT30G-50		Amphenol	
UNLESS OTHERWISE SPECIFIED TOLERANCES										APPROVED DATE 10-11-01'			
5	HEX NUT	NOTE 1	NOTE 3	1	HN127-3/8-24X2	0.5-6 = ±0.2	CHECKED DATE 10-11-01'		DRAWING NO. KJ-MU6451B1-NT30G-50		ITEM NO.		
4	LOCK WASHER	NOTE 2	NOTE 3	1	LW-127/97X05	6-30 = ±0.4	DRAWN DATE 10-11-01'						
3	CONTACT PIN	NOTE 4	NOTE 5	1	MU7530-3T	30-120 = ±0.6	FILE NO						
2	INSULATOR	NOTE 6	NATURAL	1	MU7531-2T-50	120-315 = ±1							
1	BODY	NOTE 1	NOTE 3	1	MU7531-1	315-1000 = ±1.6							
						1000-2000 = ±2.4							
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWING NO.	SCALE	4/1	ISSUE	A				