



8000-X2243 Product Details

[Share](#) | [Print](#) | [Email](#)


High Performance Solid State Relays

Not EU RoHS or ELV Compliant

Product Highlights:

- Output Voltage Rating (DC Relays) = 50 VDC
- Output Current Rating = 25 A
- Insulation - Initial Dielectric Between Contacts and Coil = 1000 V rms
- Input Voltage = 3.8 - 7 VDC
- Input Current Max. @ 5Vdc = 20 VDC

[View all Features](#)

Quick Links

- ▶ [Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

8000-X2243
(1-1617067-0)

TE Internal Number: 1-1617067-0

Superseded

[Search for Replacement Parts](#)

[Add to My Part List](#)
[Request Sample](#)
[Find Similar Products](#)
[Buy Product](#)

Documentation & Additional Information

<p>Product Drawings:</p> <ul style="list-style-type: none"> • None Available <p>Catalog Pages/Data Sheets:</p> <ul style="list-style-type: none"> • None Available <p>Product Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Application Specifications:</p> <ul style="list-style-type: none"> • None Available <p>Instruction Sheets:</p> <ul style="list-style-type: none"> • None Available <p>CAD Files:</p> <ul style="list-style-type: none"> • None Available 	<p>Additional Information:</p> <ul style="list-style-type: none"> • Product Line Information <p>Related Products:</p> <ul style="list-style-type: none"> • Tooling
---	--

Feedback

Product Features (Please use the Product Drawing for all design activity)

<p>Mechanical Attachment:</p> <ul style="list-style-type: none"> • Mounting Options = Panel Mount <p>Electrical Characteristics:</p> <ul style="list-style-type: none"> • Output Voltage Rating (DC Relays) (VDC) = 50 • Output Current Rating (A) = 25 • Insulation - Initial Dielectric Between Contacts and Coil (V rms) = 1000 • Input Voltage (VDC) = 3.8 - 7 • Input Current Max. @ 5Vdc (VDC) = 20 • Shock = 100G's, 6ms • Vibration = 30G's, 10 to 3000Hz <p>Termination Features:</p> <ul style="list-style-type: none"> • Termination Type = Solder Hooks 	<p>Body Features:</p> <ul style="list-style-type: none"> • Screening Level = W • Enclosure Type = Sealed • Packaging Style = Panel Mount <p>Industry Standards:</p> <ul style="list-style-type: none"> • Government/Industry Qualification = No • RoHS/ELV Compliance = Not ELV/RoHS compliant • Lead Free Solder Processes = Not suitable for lead free processing <p>Environmental:</p> <ul style="list-style-type: none"> • Operating Temperature Range (°C) = -55 - +85 <p>Other:</p> <ul style="list-style-type: none"> • Additional Features = Designed for Squib Firing Applications • Brand = CII
---	--

Corporate Information

- [About TE](#)
- [Investors](#)
- [News Room](#)
- [Supplier Portal](#)
- [Careers](#)
- [Terms & Conditions](#)
- [Privacy Policy](#)
- [AODA Accessibility Policy](#)
- [AODA Multi-Year Accessibility Plan](#)

Quick Links

- [Distributor Inventory](#)
- [Product Cross Reference](#)
- [Documents & Drawings](#)
- [Product Compliance Support Center](#)
- [Site Map](#)

Customer Support

- [Email or Chat With Us](#)
- [Find a Phone Number](#)
- [Knowledge Base](#)
- [Manage Your Account](#)

Keep Me Informed



