

MINI-UHF SERIES

Connectors are designed for use as coaxial interconnections in cellular mobile telephone systems and similar applications where size, weight and cost factors are critical. These miniature 3/8"-24 thread size connectors provide an excellent RF performance for applications up to 2.5 GHz. This far out performs the limit of 300 MHz. For the standard 5/8"-24 thread UHF connectors. Mini UHF connectors combine excellent electrical characteristics, small size and lightweight at a relatively inexpensive cost for many coaxial connector applications

2760 SERIES.

JACK CRIMP

Part Number	Ω	Cable
2760-11501	50	RG-58

JACK SOLDER BULKHEAD

Part Number	Ω
2760-11556	50

RECOMMENDED HOLE PATTERN

JACK SOLDER PANEL

Part Number	Ω
2760-11557	50

RECOMMENDED HOLE PATTERN

PLUG CRIMP


Part Number	Ω	Cable
2760-11502	50	RG-58

MINI UHF SERIES




2760 SERIES.

PLUG CRIMP RIGHT ANGLE



Part Number	Ω	Cable
2760-11503	50	RG-58

JACK PANEL CRIMP



Part Number	Ω	Cable
2760-13504	50	RG-174

4 Pcs.

RECOMMENDED HOLE PATTERN

