


Description

**BNC 50 Ohm Cable Jack -
Single Hole Mount Short Crimp Straight**



Ordering Data


BNC 50 Ohm Cable Jack - Single Hole Mount Short Crimp Straight

Part Number	Cable RG-/U	Crimp Tool Hex		Dimension						Finish	Mtg. Hole	Assembly Instructions	Note
				A		B		C					
		mm	in.	mm	in.	mm	in.	mm	in.				
28JS126-1	58, 141	5.41	0.213	33.34	1.313	17.07	0.672	17.46	0.688	Silver	D4	AI-26	
28JS126-2	59, 62, 140	6.48	0.255	33.34	1.313	17.07	0.672	17.46	0.688	Silver	D4	AI-26	
28JS126-3	55, 142, 223	5.41	0.213	33.34	1.313	17.07	0.672	17.46	0.688	Silver	D4	AI-26	
28JS126-6	122, 180, 195	4.52	0.178	33.34	1.313	17.07	0.672	17.46	0.688	Silver	D4	AI-26	
28JS198-1	58	5.41	0.213	34.93	1.375	20.64	0.813	17.46	0.688	Nickel	D4	AI-118	1
28JS198-2	59, 62, 210	6.48	0.255	34.93	1.375	20.64	0.813	17.46	0.688	Nickel	D4	AI-118	1
28JS198-3	180, 195	4.52	0.178	34.93	1.375	20.64	0.813	17.46	0.688	Nickel	D4	AI-118	1
28JS204-1	174, 188, 316	4.52	0.178	34.93	1.375	19.05	0.750	17.46	0.688	Nickel	D4	AI-126	1

Note 1 - Crimp Captive Contact

Description

**BNC 50 Ohm Cable Jack -
Single Hole Mount Solder Straight**



Ordering Data

BNC 50 Ohm Cable Jack - Single Hole Mount Solder Straight

Part Number	Cable RG-/U	Dimension				Finish	Mtg. Hole	Assembly Instructions
		A		B				
		mm	in.	mm	in.			
28JS155-1	0.085 OD SR	23.02	0.906	14.29	0.563	Nickel	D8	AI-65
28JS155-2	0.141 OD SR	23.02	0.906	14.29	0.563	Nickel	D8	AI-65