



STAMP: KINGS KD-59-44

STAMP: PAT. 3195098

REVISIONS	
ISSUE	CHANGES
1.	CN 2310 A 1 JUL 64
2.	CN 5860 A J.M. 20 APR 68
3.	CN 9882 A O.S. 20 AUG. 71
4.	CN 31044 C KH 9 AUG 89

KD-59-44

**NOTES:**

1. FOR USE WITH RG-58, 58A & 58C/U CABLE.
2. FOR CABLE TRIMMING USE KTJ-18 & KTD-88.
3. FOR CRIMPING USE DIE SIZE 01.
4. FOR CABLING INSTRUCTIONS SEE CP-202 A.
5. MARK PACKAGE: KINGS KD-59-44  
XXXX (DATE CODE)

-	1	BODY	
14	1	CLAMP NUT	631-4
13	1	FERRULE	N-59-29-2
12	1	GLAND	S-83-32-1
11	1	GASKET	704-6
10	1	K-GRIP	N-59-29-1
9	-	BODY ASSEMBLY	
8	2	HALF WASHER	
7	3	SPRING WASHER	
6	1	WASHER	
5	1	GASKET	
-	1	CONTACT	
3	1	INSULATOR	
2	1	BAYONET SLEEVE	
1	1	CONTACT	709-2
ITEM	REQD.	DESCRIPTION	DWG. NO.

REF:	
FINISH	
SPEC.	
MATL.	
SPEC.	
<b>C PLUG</b>	
DRAWN	LI
DATE	1 FEB 62
APPR.	
<b>KINGS ELECTRONICS</b> 40 MARLBOROUGH ROAD TUCKAHOE, N. Y.	
<b>KD-59-44</b>	

**UNLESS OTHERWISE SPECIFIED:**

- |  |  |
|--|--|
| <ol style="list-style-type: none"> <li>1. TOLERANCES:<br/>FRACTIONS ± .010 DECIMALS ± .004 ANGLES ± 0° 30'</li> <li>7. I. R. CONCENTRICITY OF ANY 2 DIAMETERS MAY NOT EXCEED THE SUM OF THEIR TOLERANCES.</li> </ol> | <ol style="list-style-type: none"> <li>2. REMOVE ALL BURRS. BREAK SHARP EDGES .003 MAX.</li> <li>3. NO FILLETS PERMITTED.</li> <li>4. SURFACE ROUGHNESS 100 MICROINCHES RMS MAX.</li> <li>5. ALL DIMENSIONS PRIOR TO PLATING.</li> </ol> |
|--|--|

DIETZGEN 199M Ageproof Tracing Yellow 7057

S-D