



FIBER OPTIC FST-SECURITY CONNECTOR




Features

- Bayonet nut connector
- One-piece design for easy and quick termination
- With integrated strain relief

Specifications

Compliance	IEC 61754-2, TIA 604-2
Technology	Full ceramic ferrule
Mechanical resistance	100 N tensile load
Thermal resistance	-40 °C to +85 °C, stock temperature range
Durability	Min. 1000 mating cycles
Adapter and connector material	Brass nickel-plated





FST-SECURITY

Ordering information: FST-Security Connector

For fiber type	Polishing	Insertion loss ¹⁾ [dB] (mean/97%)	Type
SM	PC	0.2 / 0.5	FST-SEC-A001
G50/125, G62.5/125	PC	0.25/0.70	FST-SEC-B001

2) IEC 61300-3-34

Ordering information: Adapter


Adapter type	Mounting	Sleeve material	Type
SM	with 1 loose, 1 fixed nut 1 washer for D-hole mounting	zirconia ceramic	FST-FST-C100
MM	with 1 loose, 1 fixed nut 1 washer for D-hole mounting	phosphor-bronze	FST-FST-C200

Ordering information: Accessories

Description	Color	Type
Angled boot 90° plastic (100 pieces)	green	9890.95.P

Crimpsets for FST security connector

Type	Sleeve	Boot black
Max. cable Ø		
<1.0 mm long	–	23227063
2.0 – 2.3 mm	23232995	23221232
2.4 – 2.8 mm	23231084	23221232
2.9 – 3.5 mm	23231085	23219331
3.6 – 4.5 mm	23231086	23219332



HUBER+SUHNER is certified according to ISO 9001 and ISO 14001.

Waiver

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the suitability of the products concerned for any particular use or purpose and neither shall any statement contained herein be construed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The suitability of each product for any particular purpose must be checked beforehand with our specialists.

HUBER+SUHNER - Excellence in Connectivity Solutions



HUBER+SUHNER AG
Fiber Optics Division
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 46 47
www.hubersuhner.com