


## FEATURES

- \* Short Circuit rated 10uS @Tc=100°C
- \* High Speed Switching
- \* Low Saturation Volatge  
:  $V_{CE(sat)} = 2.0\text{ V @ } I_c=5\text{A}$
- \* High Input Impedance

## APPLICATIONS

- \* AC & DC Motor controls
- \* General Purpose Inverters
- \* Robotics , Servo Controls
- \* Power Supply
- \* Lamp Ballast

D<sup>2</sup>-PAK



## ABSOLUTE MAXIMUM RATINGS

Symbol	Characteristics	Rating	Units
$V_{CES}$	Collector-Emitter Voltage	600	V
$V_{GES}$	Gate-Emitter Voltage	$\pm 20$	V
$I_c$	Collector Current @ $T_c = 25^\circ\text{C}$	8	A
	Collector Current @ $T_c = 100^\circ\text{C}$	5	A
$I_{CM(1)}$	Pulsed Collector Current	15	A
$P_c$	Maximum Power Dissipation @ $T_c = 25^\circ\text{C}$	60	W
	Maximum Power Dissipation @ $T_c = 100^\circ\text{C}$	25	W
Tsc	Short Circuit Withstand Time	10	uS
$T_j$	Operating Junction Temperature	-55 ~ 150	°C
Tstg	Storage Temperature Range	-55 ~ 150	°C
TL	Maximum Lead Temp. For Soldering	300	°C
	Purposes, $\frac{1}{8}$ " from case for 5 seconds		

**Notes:** (1) Repetitive rating : Pulse width limited by max. junction temperature

**ELECTRICAL CHARACTERISTICS**

(T<sub>c</sub>=25 °C, Unless Otherwise Specified)

Symbol	Characteristics	Test Conditions	Min	Typ	Max	Units
BV <sub>CES</sub>	C - E Breakdown Voltage	V <sub>GE</sub> = 0V , I <sub>C</sub> = 250μA	600	-	-	V
ΔV <sub>CES</sub> / ΔT <sub>J</sub>	Temperature Coeff. of Breakdown Voltage	V <sub>GE</sub> = 0V , I <sub>C</sub> = 1mA	-	0.6	-	V/°C
V <sub>GE(th)</sub>	G - E threshold voltage	I <sub>C</sub> = 5mA , V <sub>CE</sub> = V <sub>GE</sub>	5.0	6.0	8.0	V
I <sub>CES</sub>	Collector cutoff Current	V <sub>CE</sub> = V <sub>CES</sub> , V <sub>GE</sub> = 0V	-	-	250	μA
I <sub>GES</sub>	G - E leakage Current	V <sub>GE</sub> = V <sub>GES</sub> , V <sub>CE</sub> = 0V	-	-	100	nA
V <sub>CE(sat)</sub>	Collector to Emitter saturation voltage	I <sub>C</sub> =5A, V <sub>GE</sub> = 15V	-	2.0	2.7	V
		I <sub>C</sub> =8A, V <sub>GE</sub> = 15V	-	2.5	-	V
C <sub>ies</sub>	Input capacitance	V <sub>GE</sub> = 0V , f = 1MHz	-	337	-	pF
C <sub>oes</sub>	Output capacitance	V <sub>CE</sub> = 30V	-	36	-	pF
C <sub>res</sub>	Reverse transfer capacitance		-	13	-	pF
td(on)	Turn on delay time	V <sub>CC</sub> = 300V , I <sub>C</sub> = 5A	-	9	-	nS
tr	Turn on rise time	V <sub>GE</sub> = 15V	-	18	-	nS
td(off)	Turn off delay time	R <sub>G</sub> = 40 Ω	-	46	75	nS
tf	Turn off fall time	Inductive Load	-	140	280	nS
E <sub>on</sub>	Turn on Switching Loss		-	80	-	μJ
E <sub>off</sub>	Turn off Switching Loss		-	100	-	μJ
E <sub>ts</sub>	Total Switching Loss		-	180	270	μJ
T <sub>sc</sub>	Short Circuit withstand Time	V <sub>CC</sub> = 300V, V <sub>GE</sub> = 15V @T <sub>c</sub> = 100 °C	10	-	-	μS
Q <sub>g</sub>	Total Gate Charge	V <sub>CC</sub> = 300V	-	24	36	nC
Q <sub>ge</sub>	Gate-Emitter Charge	V <sub>GE</sub> = 15V	-	7	10	nC
Q <sub>gc</sub>	Gate-Collector Charge	I <sub>C</sub> = 5A	-	8	12	nC

2

**THERMAL RESISTANCE**

<b>Symbol</b>	<b>Characteristics</b>	<b>Min</b>	<b>Typ</b>	<b>Max</b>	<b>Units</b>
$R_{\theta JC}$	Junction-to-Case	-	-	2.0	$^{\circ}\text{C}/\text{W}$
$R_{\theta JA}$	Junction-to-Ambient (PCB mount)	-	-	40	$^{\circ}\text{C}/\text{W}$




Fig.1 Typical Load Current vs. Frequency




Fig.2 Typical Output Characteristics




Fig.3 Maximum Collector Current vs. Case Temperature




Fig.4 Collector to Emitter Voltage vs. Case Temperature

2




Fig.5 Maximum Effective Transient Thermal Impedance, Junction to Case




Fig.6 Typical Capacitance vs. Collector to Emitter Voltage




Fig.7 Typical Gate Charge vs. Gate to Emitter Voltage




Fig.8 Typical Switching Loss vs. Gate Resistance




Fig.9 Typical Switching Loss vs. Case Temperature




Fig.10 Typical Switching loss vs. Collector to Emitter Current




Fig.11 Turn-off SOA

2