

G3PO Male PCB Edge Mount

Full Detent, 0.123 Length

CORNING

Specifications

General Specifications	
Category	Edge Mounts
Impedance	50 Ω
Frequency Range	DC to 100 GHz typ.
Materials, Bodies	Beryllium Copper per ASTM B196 and or/ASTM B197
Materials, Outer Contacts	Beryllium Copper per ASTM B196 and or/ASTM B197
Materials, Center Contacts	Beryllium Copper per ASTM B196 and or/ASTM B197
Materials, Insulators	PTFE Fluorocarbon per ASTM D1710
Materials, Springs	17-7 Stainless Steel per ASTM A313-95A
Finish, Bodies	Gold plated per MIL-G-45204, Type I, Grade C, Class 1, Over Nickel Plate per SAE AMS-QQ-N-290
Finish, Contacts	Gold plated per MIL-G-45204, Type I, Grade C, Class 1, Over Nickel Plate per SAE AMS-QQ-N-290

Temperature Range	
Installation	-65 °C to 165 °C

Design - Hardware	
Dentent Type	FD
Length	0.123 in
Width	0.115 in
Leg Length	0.041 in
Diameter B	0.009 in

Mechanical Characteristics	
Mate / Demate Cycles FD	100 min
Mate / Demate Cycles LD	500 min
Mate / Demate Cycles SB	1,000 min
Force to Engage / Disengage FD	7.0 lbs. typ. / 9.0 lbs. typical
Force to Engage / Disengage LD	5.0 lbs. typ. / 7.0 lbs. typ.
Force to Engage / Disengage SB	2.5lbs.typ./1.5lbs.typ.
Tolerated Misalignment Axial	0.010 (flush to 0.010 from reference plane)
Tolerated Misalignment Radial	+ / - 0.010

G3PO Male PCB Edge Mount

Full Detent, 0.123 Length

CORNING

Electrical characteristics (at 20°C)

Insertion Loss	0.03 vf GHz
DWV at Sea Level	250 Vrms voltage
Insulation Resistance	≥ 3500 MΩ (DC)
Contact Resistance - Outer Conductor	< 2 mΩ
Contact Resistance - Inner Conductor	< 6 mΩ
VSWR	1.15 + 0.011 to 40 GHz, 1.20:1 to 40 GHz, 1.30:1 to 40 GHz

Chemical Characteristics

RoHS	Free of hazardous substances according to RoHS 2002/95/EG
------	---

Environmental Influences

Thermal Shock	MIL-STD-202, Method 107, Condition B
Salt Spray	MIL-STD-202, Method 101
Vibration	MIL-STD-202, Method 204
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106, except Step 7B

Ordering Information

Part Number	R010-L13-03
Product Description	G3PO Male PCB Edge Mount, Full Detent, 0.123 Length
EAN Code	4056418769264



Corning Optical Communications LLC • PO Box 489 • Hickory, NC 28603-0489 USA

800-743-2675 • FAX: 828-325-5060 • International: +1-828-901-5000 • www.corning.com/opcomm

A complete listing of the trademarks of Corning Optical Communications is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications is ISO 9001 certified.

© 2016 Corning Optical Communications. All rights reserved.

Corning Optical Communications RF LLC (Corning Gilbert) • 5310 W. Camelback Rd. • Glendale, AZ 85301 USA

800-528-5567 • FAX: 800-344-6358 • International: +1-623-245-1050 • www.corning.com/opcomm

Page 2 | Revision date 2016-03-03

A complete listing of the trademarks of Corning Optical Communications RF is available at www.corning.com/opcomm/trademarks. All other trademarks are the properties of their respective owners. Corning Optical Communications RF is ISO 9001

CORNING