

UNCOMPENSATED SPECIFICATIONS (guaranteed @ +25°C)

Frequency Range (GHz)	Output Power at 1dB Gain Comp (dBm) Min.	Gain (dB) Min.	Gain Flatness (dB) Max.	Gain Variation with Temp (dB/°C) Max.	Noise Figure (dB) Max.	Input and Output VSWR Max.	DC Current at +15V (mA)	Package Styles	Part Number
4.0 - 4.6	+12	11	±0.30	0.012	1.5	1.8	80	A1, A3	MLA 2546-101
		22	±0.40	0.024	1.5	1.8	160	A1, A3	MLA 2546-102
		33	±0.50	0.036	1.5	1.8	240	B1, B3	MLA 2546-103
		44	±0.50	0.050	1.5	1.8	320	B1, B3	MLA 2546-104
	+18	10	±0.30	0.012	4.0	1.6	100	A1, A3	MLA 2546-201
		20	±0.40	0.024	3.0	1.6	180	A1, A3	MLA 2546-202
		30	±0.50	0.036	3.0	1.6	260	B1, B3	MLA 2546-203
		40	±0.50	0.050	3.0	1.6	340	B1, B3	MLA 2546-204
	+21	9	±0.40	0.012	5.0	1.6	120	A1, A3	MLA 2546-301
		19	±0.50	0.024	4.0	1.6	220	A1, A3	MLA 2546-302
		29	±0.50	0.036	3.0	1.6	300	B1, B3	MLA 2546-303
		39	±0.50	0.050	3.0	1.6	380	B1, B3	MLA 2546-304
	+26	8	±0.40	0.012	6.0	1.8	200	A1, A3	MLA 2546-401
		17	±0.50	0.024	5.0	1.8	320	A1, A3	MLA 2546-402
		27	±0.50	0.036	4.0	1.8	420	B1, B3	MLA 2546-403
		37	±0.50	0.050	3.0	1.8	500	B1, B3	MLA 2546-404
	+29	7	±0.50	0.012	7.0	1.8	400	A1, A3	MLA 2546-501
		16	±0.75	0.024	6.0	1.8	600	A1, A3	MLA 2546-502
		26	±1.00	0.036	5.0	1.8	700	B1, B3	MLA 2546-503
		36	±1.00	0.050	4.0	1.8	800	B1, B3	MLA 2546-504

TEMPERATURE COMPENSATED SPECIFICATIONS (guaranteed -55°C to +95°C)

Frequency Range (GHz)	Output Power at 1dB Gain Comp (dBm) Min.	Gain (dB) Min.	Gain Flatness (dB) Max.	Gain Variation with Temp (dB/°C) Max.	Noise Figure (dB) Max.	Input and Output VSWR Max.	DC Current at +15V (mA)	Package Styles	Part Number
4.0 - 4.6	+12	9	±0.40	±0.50	2.5	1.8	80	A1, A3	MLA 2646-101
		18	±0.50	±0.75	2.5	1.8	160	A1, A3	MLA 2646-102
		27	±0.50	±1.00	2.5	1.8	240	B1, B3	MLA 2646-103
		36	±0.50	±1.50	2.5	1.8	320	B1, B3	MLA 2646-104
	+18	8	±0.40	±0.50	5.0	1.6	100	A1, A3	MLA 2646-201
		17	±0.50	±0.75	4.0	1.6	180	A1, A3	MLA 2646-202
		26	±0.50	±1.00	4.0	1.6	260	B1, B3	MLA 2646-203
		35	±0.50	±1.50	4.0	1.6	340	B1, B3	MLA 2646-204
	+21	8	±0.40	±0.50	6.0	1.6	120	A1, A3	MLA 2646-301
		17	±0.50	±0.75	5.0	1.6	220	A1, A3	MLA 2646-302
		26	±0.50	±1.00	4.0	1.6	300	B1, B3	MLA 2646-303
		35	±0.50	±1.50	4.0	1.6	380	B1, B3	MLA 2646-304
	+26	7	±0.50	±0.50	7.0	1.8	200	A1, A3	MLA 2646-401
		16	±0.50	±0.75	6.0	1.8	320	A1, A3	MLA 2646-402
		25	±0.50	±1.00	5.0	1.8	420	B1, B3	MLA 2646-403
		34	±0.50	±1.50	4.0	1.8	500	B1, B3	MLA 2646-404
	+29	6	±0.50	±0.50	8.0	1.8	400	A1, A3	MLA 2646-501
		15	±0.75	±0.75	7.0	1.8	600	A1, A3	MLA 2646-502
		23	±1.00	±1.00	6.0	1.8	700	B1, B3	MLA 2646-503
		30	±1.00	±1.50	5.0	1.8	800	B1, B3	MLA 2646-504

M/A-COM Ltd, Humphrys Road, Dunstable, Bedfordshire, LU5 4SX United Kingdom.

Europe: (44) 1344 869595

North America: 800 366 2266

Asia Pacific: (81) 3 3226 1671