

4-Bit Magnitude Comparator

The TC74HC85A is a high speed CMOS 4-BIT MAGNITUDE COMPARATOR fabricated with silicon gate C²MOS technology.




It achieves the high speed operation similar to equivalent LSTTL while maintaining the CMOS low power dissipation.

The TC74HC85A compares two 4-bit words applied to inputs A0 - A3 and B0 - B3, and provides a high voltage level on one of three outputs: A > B, A < B, or A = B.

All inputs are equipped with protection circuits against static discharge or transient excess voltage.

Features

- High Speed: $t_{PD} = 22ns$ (Typ.) at $V_{CC} = 5V$
- Low Power Dissipation: $I_{CC} = 2\mu A$ (Max.) at $T_a = 25^\circ C$
- High Noise Immunity: $V_{NIH} = V_{NIL} = 28\%V_{CC}$ (Min.)
- Output Drive Capability: 10 LSTTL Loads
- Symmetrical Output Impedance: $I_{OH} = I_{OL} = 4mA$ (Min.)
- Balanced Propagation Delays: $t_{PLH} = t_{PHL}$
- Wide Operating Voltage Range: $V_{CC(oper)} = 2V \sim 6V$
- Pin and Function Compatible with 74LS85



Truth Table

| Comparing Inputs | | | | Cascading Inputs | | | Outputs | | |
|------------------------------------|---------|---------|---------|------------------|-------|-------|---------|-------|-------|
| | | | | A > B | A < B | A = B | A > B | A < B | A = B |
| A3 > B3 | X | X | X | X | X | X | H | L | L |
| A3 = B3 | A2 > B2 | X | X | X | X | X | H | L | L |
| A3 = B3 | A2 = B2 | A1 > B1 | X | X | X | X | H | L | L |
| A3 = B3 | A2 = B2 | A2 = B1 | A0 > B0 | X | X | X | H | L | L |
| A3 = B3, A2 = B2, A1 = B1, A0 = B0 | | | | L | L | L | H | H | L |
| | | | | X | X | H | L | L | H |
| | | | | L | H | L | L | H | L |
| | | | | H | L | L | L | L | L |
| A3 = B3 | A2 = B2 | A2 = B1 | A0 < B0 | X | X | X | L | H | L |
| A3 = B3 | A2 = B2 | A1 < B1 | X | X | X | X | L | H | L |
| A3 = B3 | A2 < B2 | X | X | X | X | X | L | H | L |
| A3 < B3 | X | X | X | X | X | X | L | H | L |

X: Don't Care

Absolute Maximum Ratings

| Parameter | Symbol | Value | Unit |
|-----------------------------|-----------|-----------------------|------|
| Supply Voltage Range | V_{CC} | -0.5 ~ 7 | V |
| DC Input Voltage | V_{IN} | -0.5 ~ $V_{CC} + 0.5$ | V |
| DC Output Voltage | V_{OUT} | -0.5 ~ $V_{CC} + 0.5$ | V |
| Input Diode Current | I_{IK} | ± 20 | mA |
| Output Diode Current | I_{OK} | ± 20 | mA |
| DC Output Current | I_{OUT} | ± 25 | mA |
| DC V_{CC} /Ground Current | I_{CC} | ± 50 | mA |
| Power Dissipation | P_D | 500(DIP)*/180(MFP) | mW |
| Storage Temperature | T_{stg} | -65 ~ 150 | °C |
| Lead Temperature 10sec | T_L | 300 | °C |

*500mW in the range of $T_a = -40^\circ\text{C} \sim 65^\circ\text{C}$. From $T_a = 65^\circ\text{C}$ to 85°C a derating factor of $-10\text{mW}/^\circ\text{C}$ shall be applied until 300mW.

Recommended Operating Conditions

| Parameter | Symbol | Value | Unit |
|--------------------------|------------|--|------|
| Supply Voltage | V_{CC} | 2 ~ 6 | V |
| Input Voltage | V_{IN} | 0 ~ V_{CC} | V |
| Output Voltage | V_{OUT} | 0 ~ V_{CC} | V |
| Operating Temperature | T_{opr} | -40 ~ 85 | °C |
| Input Rise and Fall Time | t_r, t_f | 0 ~ 1000($V_{CC} = 2.0\text{V}$) 0 ~ 500($V_{CC} = 4.5\text{V}$) 0 ~ 400($V_{CC} = 6.0\text{V}$) | ns |

DC Electrical Characteristics

| Parameter | Symbol | Test Condition | $T_a = 25^\circ\text{C}$ | | | | $T_a = -40 \sim 85^\circ\text{C}$ | | Unit | |
|---------------------------|----------|-------------------------------|--|------|------|-----------|-----------------------------------|-----------|---------------|---|
| | | | V_{CC} | Min | Typ. | Max. | Min. | Max. | | |
| High-Level Input Voltage | V_{IH} | - | 2.0 | 1.5 | - | - | 1.5 | - | V | |
| | | | 4.5 | 3.15 | - | - | 3.15 | - | | |
| | | | 6.0 | 4.2 | - | - | 4.2 | - | | |
| Low-Level Input Voltage | V_{IL} | - | 2.0 | - | - | 0.5 | - | 0.5 | V | |
| | | | 4.5 | - | - | 1.35 | - | 1.35 | | |
| | | | 6.0 | - | - | 1.8 | - | 1.8 | | |
| High-Level Output Voltage | V_{OH} | $V_{IN} = V_{IH}$ or V_{IL} | $I_{OH} = -20\mu\text{A}$ | 2.0 | 1.9 | 2.0 | - | 1.9 | - | V |
| | | | | 4.5 | 4.4 | 4.5 | - | 4.4 | - | |
| | | | | 6.0 | 5.9 | 6.0 | - | 5.9 | - | |
| | | | $I_{OH} = -4\text{mA}$ $I_{OH} = -5.2\text{mA}$ | 4.5 | 4.18 | 4.31 | - | 4.13 | - | |
| | | | 6.0 | 5.68 | 5.80 | - | 5.63 | - | | |
| Low-Level Output Voltage | V_{OL} | $V_{IN} = V_{IH}$ or V_{IL} | $I_{OL} = 20\mu\text{A}$ | 2.0 | - | 0.0 | 0.1 | - | 0.1 | V |
| | | | | 4.5 | - | 0.0 | 0.1 | - | 0.1 | |
| | | | | 6.0 | - | 0.0 | 0.1 | - | 0.1 | |
| | | | $I_{OL} = 4\text{mA}$ $I_{OL} = 5.2\text{mA}$ | 4.5 | - | 0.17 | 0.26 | - | 0.33 | |
| | | | 6.0 | - | 0.18 | 0.26 | - | 0.33 | | |
| Input Leakage Current | I_{IN} | $V_{IN} = V_{CC}$ or GND | 6.0 | - | - | ± 0.1 | - | ± 1.0 | μA | |
| Quiescent Supply Current | I_{CC} | $V_{IN} = V_{CC}$ or GND | 6.0 | - | - | 4.0 | - | 40.0 | | |

AC Electrical Characteristics ($C_L = 15\text{pF}$, $V_{CC} = 5\text{V}$, $T_a = 25^\circ\text{C}$)


| Parameter | Symbol | Test Conditon | Min. | Typ. | Max. | Unit |
|--------------------------------------|------------------------|---------------|------|------|------|------|
| Output Transition Time | t_{TLH} t_{THL} | – | – | 4 | 8 | ns |
| Propagation Delay Time (A, B-OUT) | t_{PLH} t_{PHL} | – | – | 22 | 34 | |
| Propagation Delay Time (CASCADE-OUT) | t_{PLH} t_{PHL} | – | – | 10 | 18 | |

AC Electrical Characteristics ($C_L = 50\text{pF}$, Input $t_r = t_f = 6\text{ns}$)

| Parameter | Symbol | Test Condition | $T_a = 25^\circ\text{C}$ | | | $T_a = -40 \sim 85^\circ\text{C}$ | | Unit | |
|-------------------------------------|------------------------|----------------|--------------------------|-----|------|-----------------------------------|------|------|------|
| | | | V_{CC} | Min | Typ. | Max. | Min. | | Max. |
| Output Transition Time | t_{TLH} t_{THL} | – | 2.0 | – | 30 | 75 | – | 95 | ns |
| | | | 4.5 | – | 8 | 15 | – | 19 | |
| | | | 6.0 | – | 7 | 13 | – | 16 | |
| Propagation Delay Time (A,B-OUT) | t_{PLH} t_{PHL} | – | 2.0 | – | 90 | 195 | – | 245 | |
| | | | 4.5 | – | 26 | 39 | – | 49 | |
| | | | 6.0 | – | 22 | 33 | – | 42 | |
| Propagation Delay Time CASCADE-OUT) | t_{PLH} t_{PHL} | – | 2.0 | – | 40 | 110 | – | 140 | |
| | | | 4.5 | – | 13 | 22 | – | 28 | |
| | | | 6.0 | – | 11 | 19 | – | 24 | |
| Input Capacitance | C_{IN} | – | – | 5 | 10 | – | 10 | pF | |
| Power Dissipation Capacitance | $C_{PD}(1)$ | – | – | 25 | – | – | – | | |


Note (1) C_{PD} is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load.
Average operating current can be obtained by the equation:

$$I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{IN} + I_{CC}$$



Logic Diagram

(A) DATA



(B) DATA

Typical Application

| Comparing Input | Cascading Inputs | | | Output | | |
|-----------------|------------------|-------|-------|--------|-------|-------|
| | A > B | A = B | A < B | A > B | A = B | A < B |
| [A] > [B] | X | X | X | H | L | L |
| [A] = [B] | H | L | L | H | L | L |
| | X | H | X | L | H | L |
| [A] < [B] | L | L | H | L | L | H |
| | X | X | X | L | L | H |

X: Don't Care