

**TENTATIVE TOSHIBA HYBRID DIGITAL INTEGRATED CIRCUIT**  
**8,388,608-WORD BY 64-BIT SYNCHRONOUS DRAM MODULE**  
**DESCRIPTION**


The THMY6480D1EG is a 8,388,608-word by 64-bit synchronous dynamic RAM module consisting of eight TC59S6408FT DRAMs and an unbuffer on a printed circuit board.

**FEATURES**

- 8,388,608-word by 64-bit (single-bank) organization
- Single power supply of 3.3 V ± 0.15 V
- Pipeline architecture
- Auto-refresh and Self-refresh capability
- All inputs and outputs LVTTTL-compatible
- 4096 refresh cycles per 64 ms
- Package: 168-pin DIMM Gold contacts
- Based on Intel PC100 Rev. 0.8

	-80H
t <sub>CK</sub> Clock Cycle Time (CL = 2)	8 ns
t <sub>RAS</sub> Active-to-Precharge Command Period (min)	48 ns
t <sub>AC</sub> Access Time from CLK (CL = 2)	6 ns
t <sub>RC</sub> Ref/Active-to-Ref/Active Command Period (min)	68 ns

**PIN ASSIGNMENT (TOP VIEW)**



**PIN NAMES**


A0 to A11	Address Inputs
BA0, 1	Bank Select
DQ0 to DQ63	Data Inputs / Outputs
/CS0, 2	Chip Select
/RAS	Row Address Strobe
/CAS	Column Address Strobe
/WE	Write Enable
DQMB0 to 7	Output Disable / Write Mask
CLK0, 2	Clock Input
CKE	Clock Enable
SDA	Serial Data / Address for PD
SCL	Clock for PD
SA0 to 2	Address for PD
VDD	Power (+3.3 V)
VSS	Ground
NC	No Connection

1	VSS	85	VSS	29	DQMB1	113	DQMB5	57	DQ18	141	DQ50
2	DQ0	86	DQ32	30	/CS0	114	NC	58	DQ19	142	DQ51
3	DQ1	87	DQ33	31	NC	115	/RAS	59	VDD	143	VDD
4	DQ2	88	DQ34	32	VSS	116	VSS	60	DQ20	144	DQ52
5	DQ3	89	DQ35	33	A0	117	A1	61	NC	145	NC
6	VDD	90	VDD	34	A2	118	A3	62	NC	146	NC
7	DQ4	91	DQ36	35	A4	119	A5	63	NC	147	NC
8	DQ5	92	DQ37	36	A6	120	A7	64	VSS	148	VSS
9	DQ6	93	DQ38	37	A8	121	A9	65	DQ21	149	DQ53
10	DQ7	94	DQ39	38	A10	122	BA0	66	DQ22	150	DQ54
11	DQ8	95	DQ40	39	BA1	123	A11	67	DQ23	151	DQ55
12	VSS	96	VSS	40	VDD	124	VDD	68	VSS	152	VSS
13	DQ9	97	DQ41	41	VDD	125	CLK1	69	DQ24	153	DQ56
14	DQ10	98	DQ42	42	CLK0	126	NC	70	DQ25	154	DQ57
15	DQ11	99	DQ43	43	VSS	127	VSS	71	DQ26	155	DQ58
16	DQ12	100	DQ44	44	NC	128	CKE	72	DQ27	156	DQ59
17	DQ13	101	DQ45	45	/CS2	129	NC	73	VDD	157	VDD
18	VDD	102	VDD	46	DQMB2	130	DQMB6	74	DQ28	158	DQ60
19	DQ14	103	DQ46	47	DQMB3	131	DQMB7	75	DQ29	159	DQ61
20	DQ15	104	DQ47	48	NC	132	NC	76	DQ30	160	DQ62
21	NC	105	NC	49	VDD	133	VDD	77	DQ31	161	DQ63
22	NC	106	NC	50	NC	134	NC	78	VSS	162	VSS
23	VSS	107	VSS	51	NC	135	NC	79	CLK2	163	CLK3
24	NC	108	NC	52	NC	136	NC	80	NC	164	NC
25	NC	109	NC	53	NC	137	NC	81	NC (WP)	165	SA0
26	VDD	110	VDD	54	VSS	138	VSS	82	SDA	166	SA1
27	/WE	111	/CAS	55	DQ16	139	DQ48	83	SCL	167	SA2
28	DQMB0	112	DQMB4	56	DQ17	140	DQ49	84	VDD	168	VDD

961001EBA†

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.


**SERIAL PRESENCE DETECT (REV. 1)**

Byte Number	Function Described	Entry Value	Entry
0	Defines # Bytes Written into Serial Memory at Module mfg	128 Bytes	80h
1	Total # Bytes in SPD Memory Device	256 Bytes	08h
2	Fundamental Memory Type (FPM, EDO, SDRAM...) from Appendix A	SDRAM	04h
3	# Row Addresses on this Assembly	RA0-RA11	0Ch
4	# Column Addresses on this Assembly	CA0-CA8	09h
5	# Module Banks on this Assembly	1 Bank	01h
6	Data Width of this Assembly...	x64	40h
7	...Data Width Continuation	x64	00h
8	Voltage Interface Standard for this Assembly	LVTTTL	01h
9	SDRAM Cycle Time at Max. Supported CAS Latency (CL), CL = X	CL = 3, 8.0 ns	80h
10	SDRAM Access from Clock @ CL = X	CL = 3, 6.0 ns	60h
11	DIMM Configuration Type (Non-parity, Parity, ECC)	Non-Parity	00h
12	Refresh Rate/Type	15.625 $\mu$ s/Self-Refresh	80h
13	SDRAM Width, Primary DRAM	x8	08h
14	Error Checking SDRAM Data Width	N/A	00h
15	Minimum Clock Delay, Back-to-Back Random Column Addresses	1 CLK 	01h
16	Burst Lengths Supported	1,2,4,8 Full page	8Fh
17	# Banks on Each SDRAM Device	4 Banks	04h
18	CAS # Latencies Supported	2,3	06h
19	CS # Latency		01h
20	WE # Latency		01h
21	SDRAM Module Attributes		00h
22	SDRAM Device Attributes: General		0Eh
23	Minimum Clock Cycle Time at CL- X-1	CL = 2, 10 ns	A0h
24	Maximum Data Access Time from Clock @ CL X-1	CL = 2, 6.0 ns	60h
25	Minimum Clock Cycle Time at CL X-2		00h
26	Maximum Data Access Time from Clock @ CL X-2		00h
27	Minimum Row Precharge Time	20 ns	14h
28	Minimum Row-Active-to-Row-Active Delay	20 ns	14h
29	Minimum RAS-to-CAS Delay	20 ns	14h
30	Minimum RAS Pulse Width	50 ns	32h
31	Module/Bank Density	64 MB	10h
32-61	Superset Information (May Be Used in Future)		FFh
62	SPD Revision	Rev. 1	01h
63	Checksum for Bytes 0-62	2256h	56h

**OPTION**

64	Manufacturers JEDEC ID Code per JEP-106E		
65-71			
72	Manufacturing Location		
73-90	Manufacturer's Part Number		
91-92	Revision Code		
93-94	Date of Manufacture		
95-98	Assembly Serial Number		
99-125	Manufacturer-Specific Data		
126	Reserved	Intel Specification	66h
127	Reserved	Intel Specification	06h
128-255			

BLOCK DIAGRAM



5/

**ABSOLUTE MAXIMUM RATINGS**

SYMBOL	ITEM	RATING	UNIT	NOTES
V <sub>IN</sub>	Input Voltage	- 0.3 to V <sub>CC</sub> + 0.3	V	1
V <sub>OUT</sub>	Output Voltage	- 0.3 to V <sub>CC</sub> + 0.3	V	1
V <sub>DD</sub>	Power Supply Voltage	- 0.3 to 4.6	V	1
T <sub>OPR</sub>	Operating Temperature	0 to 70	°C	1
T <sub>STG</sub>	Storage Temperature	- 55 to 125	°C	1
P <sub>D</sub>	Power Dissipation	9.0	W	1
I <sub>OUT</sub>	Short Circuit Output Current	50	mA	1

**RECOMMENDED DC OPERATING CONDITIONS (Ta = 0° to 70°C)**

SYMBOL	PARAMETER	MIN	TYP.	MAX	UNIT	NOTES
V <sub>DD</sub>	Supply Voltage	3.15	3.3	3.45	V	2
V <sub>IH</sub>	LVTTL Input High Voltage	2.0	-	V <sub>DD</sub> + 0.3	V	2
V <sub>IL</sub>	LVTTL Input Low Voltage	- 0.3	-	0.8	V	2

**CAPACITANCE (V<sub>CC</sub> = 3.3 V, f = 1 MHz, Ta = 25°C)**

SYMBOL	PARAMETER	MIN	MAX	UNIT
C <sub>1</sub>	Input Capacitance (A0 to A11)	-	T.B.D.	pF
C <sub>2</sub>	Input Capacitance (RAS, CAS, WE, BA0,1)	-	T.B.D.	pF
C <sub>3</sub>	Input Capacitance (CLK0,2)	-	T.B.D.	pF
C <sub>4</sub>	Input Capacitance (CS0,2)	-	T.B.D.	pF
C <sub>5</sub>	Input Capacitance (DQMB0 to 7)	-	T.B.D.	pF
C <sub>DQ</sub>	I / O Capacitance (DQ0 to DQ63, CB0 to 7)	-	T.B.D.	pF

61

**DC CHARACTERISTICS** ( $V_{CC} = 3.3\text{ V} \pm 0.15\text{ V}$ ,  $T_a = 0^\circ$  to  $70^\circ\text{C}$ )

SYMBOL	ITEM	MIN	MAX	UNIT	NOTES	
$I_{CC1}$	OPERATING CURRENT Active-Precharge Command Cycling without Burst Operation ( $t_{CK} = \text{min}$ , $t_{RC} = \text{min}$ )	1-Bank Operation	-	1040	mA	3
$I_{CC2}$	STANDBY CURRENT ( $t_{CK} = \text{min}$ , $\overline{CS} = V_{IH}$ , $V_{IH}/L = V_{IH}(\text{min})/V_{IL}(\text{max})$ ) Bank: Inactive State)	CKE = $V_{IH}$	-	480	mA	3
$I_{CC2P}$		CKE = $V_{IL}$ (Power-down Mode)	-	24		
$I_{CC2S}$	STANDBY CURRENT (CLK = $V_{IL}$ , $\overline{CS} = V_{IH}$ , $V_{IH}/L = V_{IH}(\text{min})/V_{IL}(\text{max})$ ) Bank: Inactive State)	CKE = $V_{IH}$	-	40	mA	
$I_{CC2PS}$		CKE = $V_{IL}$ (Power-down Mode)	-	16		
$I_{CC3}$	NO OPERATING CURRENT ( $t_{CK} = \text{min}$ , $\overline{CS} = V_{IH}(\text{min})$ ) Bank: Active State (2 banks))	CKE = $V_{IH}$	-	720	mA	3
$I_{CC3P}$		CKE = $V_{IL}$ (Power-down Mode)	-	64		
$I_{CC4}$	BURST OPERATING CURRENT ( $t_{CK} = \text{min}$ , $\overline{CS} = V_{IH}(\text{min})$ , Read / Write Command Cycling)		-	1680	mA	3, 4
$I_{CC5}$	AUTO-REFRESH CURRENT ( $t_{CK} = \text{min}$ , $t_{RC} = \text{min}$ , Auto-Refresh Command Cycling)		-	1200	mA	3
$I_{CC6}$	SELF-REFRESH CURRENT (Self-Refresh Mode, CKE = 0.2 V)		-	3.6	mA	3
$I_{I(L)}$	INPUT LEAKAGE CURRENT ( $0\text{ V} \leq V_{IN} \leq V_{DD}$ , All Other Pins Not under Test = 0 V)		-5	5	$\mu\text{A}$	
$I_{O(L)}$	OUTPUT LEAKAGE CURRENT ( $D_{OUT}$ Is Disabled, $0\text{ V} \leq V_{OUT} \leq V_{DD}$ )		-5	5	$\mu\text{A}$	
$V_{OH}$	OUTPUT LEVEL LVTTTL Output H Level Voltage ( $I_{OUT} = -2\text{ mA}$ )		2.4	-	V	
$V_{OL}$	OUTPUT LEVEL LVTTTL Output L Level Voltage ( $I_{OUT} = 2\text{ mA}$ )		-	0.4	V	

71

**AC CHARACTERISTICS AND RECOMMENDED OPERATING CONDITIONS**

( $V_{CC} = 3.3V \pm 0.15V$ ,  $T_a = 0^\circ$  to  $70^\circ C$ ) (Notes 5, 6, 7)

SYMBOL	PARAMETER		MIN	MAX	UNIT	NOTES	
$t_{RC}$	Ref/Active-Ref/Active Command Period		70		ns	9	
$t_{RAS}$	Active-Precharge Command Period		50	100000			
$t_{RCD}$	Active-Read/Write Command Delay Time		20				
$t_{CCD}$	Read/Write(a)-Read/Write(b) Command Period		1		cycle		
$t_{RP}$	Precharge-Active Command Period		20		ns		
$t_{RRD}$	Active(a)-Active(b) Command Period		20				
$t_{WR}$	Write Recovery Time	CL* = 2	10				
		CL* = 3	8				
$t_{CK}$	CLK Cycle Time	CL* = 2	10	1000			
		CL* = 3	8	100			
$t_{CH}$	CLK High Level Width		3				10
$t_{CL}$	CLK Low Level Width		3				
$t_{AC}$	Access Time from CLK	CL* = 2		6			
		CL* = 3		6			
$t_{OH}$	Output Data Hold Time		3				
$t_{HZ}$	Output Data High Impedance Time		3	8			8
$t_{LZ}$	Output Data Low Impedance Time		0				
$t_{SB}$	Power-down Mode Entry Time		0	8			
$t_T$	Transition Time of CLK (Rise and Fall)		0.5	10			
$t_{DS}$	Data-in Set-up Time		2				
$t_{DH}$	Data-in Hold Time		1				
$t_{AS}$	Address Set-up Time		2				
$t_{AH}$	Address Hold Time		1				
$t_{CKS}$	CKE Set-up Time		2				
$t_{CKH}$	CKE Hold Time		1				
$t_{CMS}$	Command Set-up Time		2				
$t_{CMH}$	Command Hold Time		1				
$t_{REF}$	Refresh Time			64	ms		
$t_{RSC}$	Mode Register Set Cycle Time		16		ns	9	

\* CL is  $\overline{CAS}$  latency.



8/

**NOTES**

1. Conditions outside the limits listed under Absolute Maximum Ratings may cause permanent damage to the device.
2. All voltages are referenced to Vss.
3. These parameters depend on the cycle rate and their values are measured at the minimum cycle rate value t<sub>CK</sub> and t<sub>RC</sub>. Input signals are changed once during t<sub>CK</sub>.
4. These parameters depend on the output loading. The specified values are obtained with the output open.
5. The power-up sequence is described in Note 11.

**6. AC TEST CONDITIONS**

Reference Level of Output Signals	1.4 V/1.4 V
Output Load	See the diagram for AC Test Load (B) below
Input Signal Levels	2.4 V/0.4 V
Transition Time (Rise and Fall) of Input Signals	2 ns
Reference Level of Input Signals	1.4 V




7. Transition times are measured between the V<sub>IH</sub> and V<sub>IL</sub> levels. The transition (rise and fall) of input signals has a fixed slope.
8. t<sub>HZ</sub> defines the time at which the outputs go open circuit and are not reference levels.
9. These parameters depend on the number of clock cycles and depend on the operating frequency of the clock as follows:

Number of clock cycles = Specified value of timing / Clock period  
 (Round up fractions to a whole number.)

10.  $t_{CH}$  is the pulse width of CLK measured from the positive edge to the negative edge and referenced to  $V_{IH}$  (min).  $t_{CL}$  is the pulse width of CLK measured from the negative edge to the positive edge and referenced to  $V_{IL}$  (max).
11. Power-up Sequence  
Power-up must be performed in the following sequence.
- 1) Power must be applied to  $V_{DD}$  with all input signals held in the NOP state. The CLK signal must be started at the same time as power is applied.
  - 2) After power-up a pause of at least 200  $\mu$ seconds is required. Then, DQMB and CKE must be held High (at the  $V_{DD}$  level) to ensure that the DQ and CB outputs are high-impedance.
  - 3) Both banks must be precharged.
  - 4) The Mode Register Set command must be asserted to initialize the Mode register.
  - 5) An Auto-Refresh operation must consist of at least eight Auto-Refresh cycles.
- The order in which 4) and 5) are performed is interchangeable.


**TIMING DIAGRAMS**

**Read Timing**



11/


Command Input Timing




12/

Control Timing for Input Data

(Word Mask)




(Clock Mask)




Control Timing for Output Data


(Output Enable)



(Clock Mask)



Mode Register Set Cycle



A0	Burst Length	
A1	Burst Length	
A2	Burst Length	
A3	Addressing Mode	
A4	CAS Latency	
A5	CAS Latency	
A6	CAS Latency	
A7	0	(Test Mode)
A8	0	Reserved
A9	Write Mode	
A10	0	Reserved
A11	0	
BA0	0	
BA1	0	

			Burst Length	
A2	A1	A0	Sequential	Interleave
0	0	0	1	1
0	0	1	2	2
0	1	0	4	4
0	1	1	8	8
1	0	0	Reserved	Reserved
1	0	1		
1	1	0	Full Page	Reserved
1	1	1		

A3	Addressing Mode
0	Sequential
1	Interleave

A6	A5	A4	CAS Latency
0	0	0	Reserved
0	0	1	Reserved
0	1	0	2
0	1	1	3
1	0	0	4


A9	Single-Write Mode
0	Burst Read and Burst Write
1	Burst Read and Single Write

Next Command

14/14

**PACKAGE DIMENSIONS (THMY6480D1EG)**

Unit: mm



**CONTACT DIMENSIONS**

A: Unbuffered keying

B: 3.3-V keying

