



SPECIFICATIONS:
 RATING: 12V DC @ 1A
 WITHSTAND VOLTAGE:
 500V AC FOR 1 MINUTE
 INSERTION FORCE:
 BEFORE TEST OR INITIAL: 0.5KG TO 3KG
 AFTER LIFE TEST: 0.3KG TO 3KG
 EXTRACTION FORCE:
 BEFORE TEST OR INITIAL: 0.5KG TO 3KG
 AFTER LIFE TEST: 0.3KG TO 3KG
 INSULATION RESISTANCE:
 100 MEGA-OHMS MIN. @ 500V DC
 CONTACT RESISTANCE: 100mA AND @ FREQ. OF 1KHZ
 BEFORE TEST OR INITIAL: 30 MILLI-OHMS MAX
 AFTER LIFE TEST: 60 MILLI-OHMS MAX AT BELOW
 100mA AND @ FREQ. OF 1KHZ
 LIFE TEST:
 5,000 CYCLES OF INSERTION AND EXTRACTION
 @ 20 TO 30 CYCLES PER MINUTE UNDER NO LOAD

CUI STACK
 9615 SW Allen, Suite 103
 Beaverton, OR 97006
 Phone: (503) 643-4899
 Fax: (503) 643-6129
 Website: www.cuistack.com

TITLE: 6.4mm AUDIO JACK-STEREO	
PART NO. SJ-6363N	UNITS: MM [INCHES]
DRAWN BY:	APPROVED BY:
	SCALE: 2X