



Type No.	Reliability Option	Polarity	Package	V _{CEO}	I _c cont	h _{FE} @	V _{CE} /I _c	f _T	P _D
BC303-4	SCREEN	PNP	TO39	60	1	40-80	10/0.15	75M	0.85
BC303-5	SCREEN	PNP	TO39	60	1	70-140	10/0.15	75M	0.85
BC303-6	SCREEN	PNP	TO39	60	1	120-240	10/0.15	75M	0.85
BC304	SCREEN	PNP	TO39	45	1	40-240	10/0.15	75M	0.85
BC307		PNP	TO92	45	0.1	75min	5/2m	150M	0.3
BC307A		PNP	TO92	45	0.1	125min	5/2m	150M	0.3
BC307B		PNP	TO92	45	0.1	240min	5/2m	150M	0.3
BC307C		PNP	TO92	45	0.1	450min	5/2m	150M	0.3
BC308		PNP	TO92	25	0.1	75min	5/2m	150M	0.3
BC308A		PNP	TO92	25	0.1	125min	5/2m	150M	0.3
BC308B		PNP	TO92	25	0.1	240min	5/2m	150M	0.3
BC308C		PNP	TO92	25	0.1	450min	5/2m	150M	0.3
BC309		PNP	TO92	20	0.1	70-460	5/2m	150M	0.3
BC312		NPN	TO39	100	5	130typ	10/30m		0.8
BC313		PNP	TO39	40	1	40-250	1/0.15		0.8
BC315		PNP	TO92	35	0.1	100-350	5/2m	200M	0.3
BC317		NPN	TO92	45	0.15	110-450	5/2m	100M	0.31
BC317A		NPN	TO92	45	0.15	110-220	5/2m	100M	0.31
BC317B		NPN	TO92	45	0.15	200-450	5/2m	100M	0.31
BC318		NPN	TO92	30	0.15	110-800	5/2m	100M	0.31
BC318A		NPN	TO92	30	0.15	110-220	5/2m	100M	0.31
BC318B		NPN	TO92	30	0.15	200-450	5/2m	100M	0.31
BC320		NPN	TO92	45	0.15	110-450	5/2m	100M	0.31
BC320A		NPN	TO92	45	0.15	110-220	5/2m	100M	0.31
BC320B		NPN	TO92	45	0.15	200-450	5/2m	100M	0.31
BC323		NPN	TO39	100	5	50-250	1/0.5	100M	0.8
BC325		PNP	TO18	60	50m	40-120	5/10m		0.36
BC327		PNP	TO92	45	0.5	100-600	1/0.1	100M	0.6
BC327-16		PNP	TO92	45	0.8	180max	1/0.1	100M	0.6
BC327-25		PNP	TO92	45	0.8	160-400	1/0.1	100M	0.6
BC327-40		PNP	TO92	45	0.8	250-630	1/0.1	100M	0.6
BC328		PNP	TO92	25	0.5	100-600	1/0.1	100M	0.6
BC328L		PNP	TO92	25	0.5	100-600	1/0.1	100M	0.6
BC328-16		PNP	TO92	25	0.8	180max	1/0.1	100M	0.6
BC328-25		PNP	TO92	25	0.8	160-400	1/0.1	100M	0.6
BC328-40		PNP	TO92	25	0.8	250-630	1/0.1	100M	0.6
BC337		NPN	TO92	45	0.5	100-600	1/0.1	200M	0.6
BC337-16		NPN	TO92	45	0.5	180max	1/0.1	200M	0.6
BC337-25		NPN	TO92	45	0.8	160-400	1/0.1	200M	0.6
BC337-40		NPN	TO92	45	0.8	250-630	1/0.1	200M	0.6
BC338		NPN	TO92	25	0.5	100-600	1/0.1	200M	0.6
BC338-16		NPN	TO92	25	0.5	180max	1/0.1	200M	0.6
BC338-25		NPN	TO92	25	0.8	160-400	1/0.1	200M	0.6
BC338-40		NPN	TO92	25	0.8	250-630	1/0.1	200M	0.6
BC340		NPN	TO39	40	0.5	40-250	5/50m	100M	0.8