



**SPECIFICATIONS**

- Zinc alloy die cast housing and cylinder
- Bright chrome plated standard
- 4 pin tumbler mechanism
- Steel tubular keys, nickel plated
- Key-pull in both positions
- Silver plated contacts and terminals
- 2 positions (on-on), 4 terminals
- Hex nut mounted
- All keyed alike or one combination per 100pcs standard
- 200 key combinations available

- - Off position
- ┃ - Indicates key pull
- - Indicates no key-pull



Series	Style	Key combinations
SWTK	S146-2	X
Key lock switch	ø12mm cylinder, key-pull in both positions	A=All keyed alike B=One combination per 100pcs (up to 200 combinations) C=Customer specified

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	08/10/99
				Checked	Lizzy	08/10/99
				Drawn	Tina	08/10/99
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

**Central Components Manufacturing**  
 440 Lincoln Blvd., Middlesex, New Jersey 08846  
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWTK-S146-2-X**

Description: Micro switch lock, 12mm diameter, key-pull in both positions