




SLOTTED OPTICAL SWITCH

H21B4/5/6

PACKAGE DIMENSIONS




SYMBOL	MILLIMETERS		INCHES		NOTES
	MIN.	MAX.	MIN.	MAX.	
A	10.7	11.0	.422	.433	
A ₁	3.0	3.2	.119	.125	
A ₂	3.0	3.2	.119	.125	
b ₁	.800	.750	.024	.030	2
b ₂	.50 NOM.	.020 NOM.			2
D	24.3	24.7	.957	.972	
D ₁	11.6	12.0	.457	.472	
D ₂	3.0	3.3	.119	.129	
e ₁	6.9	7.5	.272	.295	
e ₂	2.3	2.8	.091	.110	
E	6.15	6.35	.243	.249	
L	8.00		.315		
Op	3.2	3.4	.126	.133	
Q	18.9	19.2	.745	.755	
S	.85	1.0	.034	.039	
S ₁	3.45	3.75	.136	.147	
T	2.6 NOM.		.103 NOM.		3

NOTES:

1. INCH DIMENSIONS ARE DERIVED FROM MILLIMETERS.
2. FOUR LEADS. LEAD CROSS SECTION IS CONTROLLED BETWEEN 1.27mm (.050") FROM SEATING PLANE AND THE END OF THE LEADS.
3. THE SENSING AREA IS DEFINED BY THE "S" DIMENSION AND BY DIMENSION "T" $\pm 0.75\text{mm}$ ($\pm .030$ INCH).

PACKAGE OUTLINE



DESCRIPTION

The H21B Slotted Optical Switch is a gallium arsenide light emitting diode coupled to a silicon photodarlington in a plastic housing. The packaging system is designed to optimize the mechanical resolution, coupling efficiency, ambient light rejection, cost and reliability. The gap in the housing provides a means of interrupting the signal with an opaque material, switching the output from an "ON" to an "OFF" state.

FEATURES

- Opaque housing
- Low cost
- .035" apertures
- High I_{C100}



SLOTTED OPTICAL SWITCH

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)

Storage Temperature	-55°C to +100°C
Operating Temperature	-55°C to +100°C
Soldering:	
Lead Temperature (Iron)	240°C for 5 sec. ⁽¹⁾
Lead Temperature (Flow)	260°C for 10 sec. ⁽²⁾
INPUT DIODE	
Continuous Forward Current	60 mA
Reverse Voltage	6.0 Volts
Power Dissipation	100 mW ⁽³⁾
OUTPUT DARLINGTON	
Collector-Emitter Voltage	55 Volts
Emitter-Collector Voltage	7 Volts
Power Dissipation	150 mW ⁽²⁾

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless Otherwise Specified)

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
INPUT DIODE						
Forward Voltage	V_F	---	---	1.7	V	$I_F = 60 \text{ mA}$
Reverse Breakdown Voltage	V_R	6.0	---	---	V	$I_R = 10 \mu\text{A}$
Reverse Leakage Current	I_R	---	---	1.0	μA	$V_R = 3 \text{ V}$
OUTPUT DARLINGTON						
Emitter-Collector Breakdown	BV_{CEO}	7.0	---	---	V	$I_C = 100 \mu\text{A}, Ee = 0$
Collector-Emitter Breakdown	BV_{ECD}	55	---	---	V	$I_C = 1 \text{ mA}, Ee = 0$
Collector-Emitter Leakage	I_{CEO}	---	---	100	nA	$V_{DC} = 45 \text{ V}, Ee = 0$
<b b="" coupled<="">						
On-State Collector Current	I_{CDS}	---	See page 3.	---	mA	
Saturation Voltage	$V_{CE(SAT)}$	---	See page 3.	---	V	
Turn-On Time	t_{on}	---	See page 3.	---	μs	
Turn-Off Time	t_{off}	---	See page 3.	---	μs	

NOTES

- Derate power dissipation linearly 1.33 mW/ $^\circ\text{C}$ above 25°C.
- Derate power dissipation linearly 2.00 mW/ $^\circ\text{C}$ above 25°C.
- RMA flux is recommended.
- Methanol or Isopropyl alcohols are recommended as cleaning agents.
- Soldering iron tip $1/8''$ (1.6 mm) from housing.



SLOTTED OPTICAL SWITCH

ELECTRICAL V _{CE(SAT)} , I _C , AND T _{ON}						
PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNITS	TEST CONDITIONS
ON-STATE COLLECTOR CURRENT						
H21B4	I _{CO4}	0.5	—	—	mA	I _r = 2mA, V _{ce} = 1.5V
H21B5	I _{CO5}	1.0	—	—	mA	I _r = 2mA, V _{ce} = 1.5V
H21B6	I _{CO6}	2.0	—	—	mA	I _r = 2mA, V _{ce} = 1.5V
H21B4	I _{CO4}	2.5	—	—	mA	I _r = 5mA, V _{ce} = 1.5V
H21B5	I _{CO5}	5.0	—	—	mA	I _r = 5mA, V _{ce} = 1.5V
H21B6	I _{CO6}	10	—	—	mA	I _r = 5mA, V _{ce} = 1.5V
H21B4	I _{CO4}	7.5	—	—	mA	I _r = 10mA, V _{ce} = 1.5V
H21B5	I _{CO5}	14	—	—	mA	I _r = 10mA, V _{ce} = 1.5V
H21B6	I _{CO6}	25	—	—	mA	I _r = 10mA, V _{ce} = 1.5V
SATURATION VOLTAGE						
H21B4	V _{CE(SAT)}	—	—	1.0	V	I _r = 10mA, I _c = 1.8mA
H21B5	V _{CE(SAT)}	—	—	1.0	V	I _r = 10mA, I _c = 1.8mA
H21B6	V _{CE(SAT)}	—	—	1.0	V	I _r = 10mA, I _c = 1.8mA
H21B5	V _{CE(SAT)}	—	—	1.5	V	I _r = 60mA, I _c = 50mA
H21B6	V _{CE(SAT)}	—	—	1.5	V	I _r = 60mA, I _c = 50mA
Turn-On Time						
H21B4, H21B5, H21B6	t _{on}	—	45	—	μS	V _{cc} = 5V, I _r = 10mA, R _L = 750Ω
H21B4, H21B5, H21B6	t _{on}	—	7	—	μS	V _{cc} = 5V, I _r = 60mA, R _L = 75Ω
Turn-Off Time						
H21B4, H21B5, H21B6	t _{off}	—	250	—	μS	V _{cc} = 5V, I _r = 10mA, R _L = 750Ω
H21B4, H21B5, H21B6	t _{off}	—	45	—	μS	V _{cc} = 5V, I _r = 60mA, R _L = 75Ω



SLOTTED OPTICAL SWITCH

TYPICAL CHARACTERISTICS




Fig. 1. Output Current vs. Input Current




Fig. 2. Output Current vs. Temperature




Fig. 3. $V_{ce(sat)}$ vs. Temperature




Fig. 4. Leakage Currents vs. Temperature




Fig. 5. Switching Speed vs. R_L




Fig. 6. Output Current vs. Shield Distance